

Finishing set for 2x single coax connection and satellite for flush mounting in trunking systems or splashproof switching materials.

101-69552

4 year warranty

Finishing set for a mechanism with two single coax connections for TV and FM. A satellite connection is also provided. This central plate is suitable for flush mounting in trunking systems or in splashproof switching materials.

Technical data

Finishing set for 2x single coax connection and satellite for flush mounting in trunking systems or splashproof switching materials.

TV connection < 1dB (5-75MHz); 1,5dB +/- 1dB (25-860MHz), connection FM < 3dB (88-108MHz), in accordance with DIN45325 and IEC 60169-2, suitable for plugs Ø9.5 mm. Satellite connection 2.5dB +/- 1dB (950-2150MHz). DC 1A, 18V DC. The contacts are shielded with a permanent metal cap. This flush-mounting socket with 2x single coax connection for TV (male) and FM (female) and satellite can be clicked directly into a mounting frame 45x45 mm, an installation channel with a cover height 45mm or in an empty Mini-Patch distributor with a 45x45mm opening. The coaxial cable is connected to the back of the mechanism. Two arrows and the dismantling length are marked on the back of the base to aid in assembly. The arrow pointing downward indicates where the coax cable has to be inserted. The coaxial cable is screwed in is screwed with a screw with mixed screwhead (crosshead-slit 1mm). The strain relief is screwed with a permanent screw with mixed screwhead (crosshead-slit 1mm). The base is fitted with two snap hooks at the bottom and top that hold the central plate in place. On each of its 4 corners, the base is equipped with studs to ensure that the central plate is perfectly positioned in relation to the to the base. The central plate is clicked onto a TV/FM + satellite socket and is engraved with 'TV' and 'FM'. The central plate is made of rigid PC+ASA. The raw material is coloured white in the mass (approximately RAL9010). The plastic components of the central plate comply with a filament test of 650°C, and they are halogen-free. Central plate dimensions: 45x45mm. CE marked

- Protection degree: IP41 for the combination of a mechanism, central plate and faceplate
- Impact resistance: The combination of a mechanism, a central plate and a faceplate has an impact-resistance of IK06
- Marking: CE

CE

