Finishing set with HDMI-to-screw connection, light grey

102-69416



Finishing set with HDMI-to-screw connection. This product is used when an HDMI cable must be concealed in a wall for the connection of a TV to a set-top box or a computer to a projector. At the back, the socket outlet is provided with a screw connector to which an HDMI cable can be connected of which the connector has been cut off at one side for pulling the cable through a conduit. For use in combination with the universal base with either screw or claw fixing.



Technical data

Finishing set with HDMI-to-screw connection, light grey.

- Function: This product is used when an HDMI cable must be concealed in a wall for the connection of
 a TV to a set-top box or a computer to a projector. At the back, the finishing set is fitted with a screw
 connector to which an HDMI cable can be connected of which the connector has been cut off at one side
 for pulling the cable through a conduit. For use in combination with the universal base with either screw or
 claw fixing.
- Material central plate: The central plate is made of rigid PC and ASA. The base material is coloured in mass.
- Colour: light grey (coloured in mass, approximately NCS S 1002 Y, RAL 080 80 05)
- Fire safety
 - The plastic parts of the central plate are self-extinguishing (comply with a filament test of 650°C)
 - The plastic parts of the central plate are halogen-free.
- Dismantling: To dismount simply pull the central plate off the base.
- Protection degree: IP41 for the combination of a mechanism, central plate and faceplate
- Impact resistance: The combination of a mechanism, a central plate and a faceplate has an impact-resistance of IK06
- Dimensions (HxWxD): 44.5 x 44.5 x 8.6 mm
- Marking: CE

