## Double faceplate with 71 mm centre-to-centre distance Niko Pure stainless steel on anthracite

## 150-76800



Double faceplate with 71 mm centre-to-centre distance from the range Finishing colour faceplate: Niko Pure stainless steel on anthracite

## **Technical data**

Double faceplate with 71 mm centre-to-centre distance Niko Pure stainless steel on anthracite.

- Double faceplate for two switches.
- Colour: stainless steel on anthracite (approximately NCS S 5502 Y, RAL 9006)
- Frame composition: It consists of an upper frame and lower frame that are mechanically interconnected.
- Material upperframe: The upperframe is made of brushed stainless steel.
- Material underframe: The lower frame is made of dark grey pc + ASA.
- Frame thickness: The upper frame is 2 mm thick and the underframe 6 mm.
- Surface-mounting height: max. 8.5 mm
- Fire safety
  - self-extinguishing: complies with a filament test of 650°C
  - halogen-free
- Protection degree: IP41 for the combination of a mechanism, central plate and faceplate
- Impact resistance: The combination of a mechanism, a central plate and a faceplate has an impact-resistance of IK06
- Dimensions (HxWxD): 83 x 154 x 8.9 mm
- Certification marks: CEBEC, KEMA, ÖVE, SEMKO, NF
- Marking: CE



