Double faceplate with 71 mm centre-to-centre distance Niko Pure steel champagne

157-76800

Double faceplate with 71 mm centre-to-centre distance from the range Finishing colour faceplate: Niko Pure steel champagne

Technical data

Double faceplate with 71 mm centre-to-centre distance Niko Pure steel champagne.

- Double faceplate for two switches.
- Colour: steel champagne (approximately NCS S 4005 Y20R, RAL 080 70 10)
- Frame composition: It consists of an upper frame and lower frame that are mechanically interconnected.
- Material upperframe: The upperframe is made of steel.
- Varnish upperframe: The upperframe is enamelled champagne.
- $\bullet\,$ Material underframe: The lower frame is made of dark grey pc + ASA.
- Frame thickness: The upper frame is 2 mm thick and the underframe 6 mm.
- Surface-mounting height: max. 8.5 mm
- Fire safety
 - self-extinguishing: complies with a filament test of 650°C
 - halogen-free
- Protection degree: IP41 for the combination of a mechanism, central plate and faceplate
- Impact resistance: The combination of a mechanism, a central plate and a faceplate has an impact-resistance of IK06
- Dimensions (HxWxD): 83 x 154 x 8.9 mm
- Certification marks: CEBEC, KEMA, ÖVE, SEMKO, NF
- Marking: CE

CE



4 year warranty



www.niko.eu