

# Threefold faceplate with 71 mm centre-to-centre distance Niko Pure alu gold

221-76700

4 year warranty

Threefold faceplate with 71 mm centre-to-centre distance from the range Finishing colour faceplate: Niko Pure alu gold

## Technical data

Threefold faceplate with 71 mm centre-to-centre distance Niko Pure alu gold.

- Threefold faceplate for three switches.
- Colour: alu gold (approximately NCS S 3020 - Y, RAL 1000)
- Frame composition: It consists of an upper frame and lower frame that are mechanically interconnected.
- Material upperframe: The upperframe is made of anodised aluminium (Alu Gold).
- Material underframe: The underframe is made from white PC + ASA.
- Frame thickness: The upper frame is 2 mm thick and the underframe 6 mm.
- Surface-mounting height: max. 8.5 mm
- Fire safety
  - self-extinguishing: complies with a filament test of 650°C
  - halogen-free
- Protection degree: IP41 for the combination of a mechanism, central plate and faceplate
- Impact resistance: The combination of a mechanism, a central plate and a faceplate has an impact-resistance of IK06
- Dimensions (HxWxD): 83 x 225 x 8.9 mm
- Certification marks: CEBEC, KEMA, NF, VDE, ÖVE, SEMKO
- Marking: CE

