

Electronic 150 W transformer, IP65, incl. rubber insulated wires on the primary side

320-00124

4 year warranty

This electronic transformer has a capacity of 150 W and is universally dimmable. It is suitable for the connection of low-voltage loads (12 V). For a quick and correct connection, you connect the cable on the primary side to a Niko mini-connection box. The silicon wire on the secondary side can be directly connected to a spotlight. This transformer is also suitable for flush mounting in furniture. It is equipped with built-in short-circuit, overload and overheating protection. The transformer has an IP65 protection degree.



Technical data

Electronic 150 W transformer, IP65, incl. rubber insulated wires on the primary side

- Efficiency in full load: 93 %
- Not intended to operate in no-load mode
- Function: electronic transformer
- Input voltage: 230 Vac \pm 10 %, 50 Hz
- Dimensions (HxWxD): 113 x 52 x 32 mm
- Primary wire connection: with rubber insulated cable: 2 x 1 mm², length 50 cm
- Secondary wire connection: with silicon-insulated wire (170 °C): 2 x 0.75 mm², length 30 cm
- Number of exits (pairs): 1
- Maximum wire length secondary connection: 2 m
- Output voltage: 11.5 Vac, 50-60 Hz
- Minimum load: 35 W
- Maximum load: 150 W
- Maximum housing temperature (T_c): 80 °C
- Minimum free space in false ceiling: 100 mm
- Application: suitable for flush-mounting in furniture
- Mounting method: flush-mounting
- Safety protections: self-resetting, built-in protection against short-circuit, overload and overheating
- Fire safety
 - self-extinguishing: complies with a filament test of 850 °C
 - suitable for normal combustible surfaces
- Protection degree: IP65
- Protection class: Class III device: SELV (safety extra low voltage), suitable as a power supply for class III loads
- Finishing colour: white
- Material upperframe: plastic
- Certification marks: ENEC
- Marking: CE
- Weight: 317 g



www.niko.eu

niko

320-00124 - 21-06-2023