Motion detector, Niko Home Control, 16 m, 180°, IP54, with orientable lens, for surface mounting, white

550-20200


This motion detector is suitable for outdoor use, for example, along the driveway, on the terrace or in the garden. It is also equipped with a built-in light sensor. You aim the motion detector wherever you wish and partition the detection area using a cover mask. The Niko Home Control system supplies power to the device. Finishing colour: white

Compatible secondary detectors: 550-20200



4 year warranty

Detection range



H ₽↔	A Across ∭r→	B Towards ∯↑
2 m	11 m	5.5 m
2.5 m	14 m	7 m
3 m	16 m	8 m





Technical data

Article number	550-20200	
Compatible secondary detectors	550-20200	
Input voltage	26 Vdc (SELV, safety extra-low voltage)	
Detector output	26 V	
Light intensity range	5 lux – ∞	
Switch-off delay	8 s – 30 min	
Detection angle	180 °	
Detection range (PIR)	16 m from a height of 3 m	
Ambient temperature	-20 - +45 °C	
Mounting method	surface mounting	
Mounting height	2 – 3 m	
Dimensions visible (HxWxD)	90 x 70 x 130 mm	
Dimensions (HxWxD)	70 x 90 x 130 mm	
Protection degree	IP54	
Marking	CE	

Accessories

390-20050 Mounting brace for outdoor motion detector, white

Dimensions

