

# Connected motor control, base, 3 A, 71 x 71 mm, screw fixing, Easywave # technology

551-72311

4 year warranty

The connected motor control contains a switching contact to control a 230 V motor. It contains a transmitter and receiver that communicate wirelessly with the wireless smart hub for Niko Home Control. You can use the connected motor control to replace a conventional motor control. The connected motor control can switch its own contacts.

With the addition of the wireless smart hub for Niko Home Control, it is possible to configure additional functionalities with the Niko Home Control programming software. For example, it becomes possible to add it to a scene or all-off function. This device is not compatible with the wireless bridge (550-00640).



## Technical data

Connected motor control, base, 3 A, 71 x 71 mm, screw fixing, Easywave # technology.

- Not compatible with the wireless bridge
- Modification of settings: Niko Home Control programming software (requires smart hub)
- Maximum range (from switch to smart hub): 30 m
  
- Maximum MCB rating: 16 A (limited by national installation rules)
- Communication protocol: Easywave #
- Maximum radio frequency power: 6 dBm
- Operating frequency: 0.8691 GHz
- Fixing method
  - with screws for simple fixing in a flush-mounting box with grip surfaces
- Centre-to-centre distance
  - horizontal coupling and vertical coupling with centre-to-centre distance 71 mm
  - horizontal connection of several bases is quick and perfect thanks to the folded-up dovetails on the left and right side
  - extra robustness due to the folded-up edges on the outside of the base and the continuation to the inside of the base
- Ambient temperature: 0 – 40 °C
- Dimensions (HxWxD): 71.5 x 73 x 40 mm
- Weight: 70 g
- Marking: CE

