

WARNING: This apparatus is designed to protect individuals from the acute effects of carbon monoxide exposure. It will not fully safeguard individuals from specific medical conditions. If in doubt consult a medical practitioner.

Product description

The Deta 1137 battery operated Carbon Monoxide alarms are ideal for the home and travelling on holiday. Its compact size takes up little room in the baggage but gives you invaluable protection from faulty heating and cooking appliances wherever you are.

Three LED's on the front of the alarm indicate Alarm (red) when the alarm has detected harmful levels of CO; Power, (green) flashes one every minute when the alarm is operating and Fault (yellow) indicates a fault in the alarm. All three LEDs operate with different sound patterns as shown in the Table 1.

CO level alarm points

The alarm will go into the alarm condition under the following circumstances:

Carbon Monoxide Level (Parts per million)	No Alarm Before	Alarm Before
30 ppm	120 mins	-
50 ppm	60 mins	90 mins
100ppm	10 mins	40 mins
300ppm	-	3 mins

What to do if the alarm sounds

If the alarm sounds a repeating series of 4 beeps, (see Table 1) evacuate the property immediately. If it is not possible for all occupants to exit the property for any reason, call for help, open all doors and windows to ventilate it and move to fresh air.

**IN THE CASE OF SUSPECTED CARBON MONOXIDE (CO) POISONING,
SEEK MEDICAL ASSISTANCE IMMEDIATELY.**

If it is safe to do so, turn off all appliances, shut off the gas supply tap and:

CALL TRANSCO ON 0800 111 999

Do not silence the alarm or re-enter the property until the source of Carbon Monoxide (CO) has been found and dealt with by a competent and registered Gas Safe engineer.

Table 1		
Carbon Monoxide Present	Repeating Series of 4 beeps with Red LED
Alarm Test	One series of 4 beep with green, yellow and red LEDs
Low Battery	One beep every minute
Fault	Two beeps every minute with red and yellow LEDs
End of alarm life	Three beeps every minute

The alarm will reset itself if the CO dissipates naturally.

Where to install your alarm

The design and layout of domestic premises and the number, type and position of carbon monoxide sources vary widely. However, general guidance is given below on where and where not to locate the alarm in order to minimise the risk of misleading indications.

Which room?

Ideally, an alarm should be installed in every room containing a fuel burning appliance. Additional alarms may be installed to ensure that adequate warning is given for occupants in other rooms, by locating alarms:

- in remote rooms in which the occupant(s) spend considerable time whilst awake and from which they may not be able hear an alarm from an alarm in another part of the premises,
- and every sleeping room.

However, if there is a fuel burning appliance in more than one room and the number of alarms is limited, the following points should be considered when deciding where best to put an alarm:

- locate an alarm in a room containing a flueless or open-flued appliance, and
- locate an alarm in a room where the occupant(s) spend most time.
- If the appliance is in a room not normally used (for example a boiler room), the alarm should be put just outside the room so that the alarm may be heard more easily. If that room is remote, then the guidance in points a. and b. above should be considered.

Where in the room?

It should be possible to view all the light indicators on the alarm when in the vicinity of its chosen location. It is not possible to give specific guidance on the exact location of an alarm which suits all types of room and their usage. The following points should be taken into consideration when determining an optimum location for any situation:

Where not to install the alarm

The alarm **SHOULD NOT** be installed:

- in an enclosed space (for example in a cupboard or behind a curtain);
- where it can be obstructed (for example by furniture, books or ornaments);
- directly above a sink;
- next to a door or window;
- next to an extractor fan;
- next to an air vent or other similar ventilation openings;
- in an area where the temperature may drop below -10°C or exceed 40°C,
- where dirt and dust may block the sensor;
- in a damp or humid location;
- in the immediate vicinity of a cooking appliance.

Consider the following when an alarm is located in the same room as a fuel burning appliance:

- If the alarm is located on a wall it should be located close to the ceiling and at a height greater than the height of any door or window.
- A ceiling mounted alarm should be at least 300 mm from any wall, and for a wall mounted alarm it should be at least 150 mm from the ceiling.
- The alarm should be at a horizontal distance of between 1 m and 3 m from the potential source. If there is a partition in a room, the alarm should be located on the same side of the partition as the potential source.
- Carbon Monoxide alarms in rooms with sloped ceilings should be located at the high side of the room.

An alarm located in sleeping rooms and in rooms remote from a fuel burning appliance:

An alarm that is located in sleeping rooms and in rooms remote from the fuel-burning appliance should be located relatively close to the breathing zone of the occupants. (The breathing zone should be regarded as the horizontal level in the room where a person's head spends most of the time, ie while sat in a chair or laid on a pillow.

Pay particular attention to the normal location of the elderly and disabled when reaching a decision. For further information contact the manufacturers helpline on **+44 (0)1582 544 548** or CoGDEN (The Council for Gas Detection and Environmental Monitoring) on their helpline **0800 1694 457**

Particular attention should be given to sleeping accommodation. Carbon Monoxide is particularly hazardous to a person while asleep as it will not wake them. If they wake and have been subjected to carbon monoxide, they may be too disorientated to know what is wrong with them and what to do next. A Carbon Monoxide alarm at the bed head will help to avoid this situation

WARNING: Do not operate this alarm in areas with temperatures less than -10°C or greater than +40°C; or in humidity less than 30% RH or more than 90% RH.

How to install your alarm

This apparatus should be installed by a competent person

As a portable Device:

- Assemble the device as shown in Figs. 1 & 2.
The alarm will automatically switch on and beep 4 times with lights and display if fitted. Test the alarm using the test button and refer to Table 1.
To remove the baseplate and turn off the alarm, see the end of this section.





- Attach the stand as shown in Fig. 3

- Place the alarm in your chosen position in free air with no local obstructions and close to the front edge of shelves and surfaces. See "Where to install the alarm" above.

Fixing the alarm to a wall:

- Decide on the position for the alarm in open air and unobstructed from the guidance given above in "Where to install the alarm".
- Using the screws and fixings supplied fix firmly to the wall as shown in Fig. 4.
Assemble the alarm to the baseplate as shown above in Fig 1. The alarm will automatically switch on and beep 4 times with lights and display if fitted.
- Test the alarm using the test button and refer to Table 1.

NOTE: To Remove the alarm from the baseplate, depress the tag fully towards the back of the baseplate and slide the alarm towards the top. See Fig 5.



How to maintain your alarm

WARNING: Tampering with this alarm may cause a malfunction

Testing the alarm

Test the alarm once a week using the test button. It should flash all three LEDs once, one after another, followed by 4 beeps from the sounder.

Cleaning the alarm

Regular cleaning of the alarm is essential if it is to work properly. Keep free of dust and vacuum it every month and ensure the vents are clear. Every six months wipe the outside with a damp cloth to remove staining and grease from cooking etc.

Battery Information

The battery is sealed in and is not replaceable. It should last 7 years; the life of the alarm. After approximately 7 years, the alarm will beep three times every minute to indicate end of life. At this point the alarm should be replaced. Extended periods in alarm mode can significantly reduce the life of the battery.

Automatic fault detection

In the unlikely event of a fault developing in your alarm, it will emit two beeps every minute (see Table 1). If this happens DO NOT OPEN THE ALARM, there are no user serviceable parts inside. Remove it from the baseplate to turn it off and return it to the manufacturer at the address at the end of this handbook.

What is carbon monoxide?

Carbon Monoxide (CO) is an extremely poisonous gas. It is a colourless, odourless and tasteless gas released by the incomplete combustion of fossil fuels such as natural gas, bottled gas, petrol, diesel, oil, paraffin, wood, coal coke and bio-fuels.

When inhaled, it causes chemical asphyxiation, when CO mixes with the blood and reduces the oxygen carried around the body, in particular to the brain. The following symptoms are typical of CO poisoning and should be discussed with all members of your household.

Mild Exposure:

Slight headache, nausea, fatigue, often thought to be flu symptoms. Think CO.

Medium Exposure:

Severe throbbing headache, drowsiness, confusion, vomiting and fast heart rate.

Extreme Exposure:

Unconsciousness, Convulsions, Cardio-respiratory failure, death.

Although feeling unwell, victims of CO poisoning become so disoriented that they can no longer decide what to do next, including being unable to exit the building or call for assistance. Very young children often show symptoms earlier than adults.

Being affected while asleep is the most dangerous situation as the victim will not wake as a result.

What are the potential sources of carbon monoxide?

A correctly operating and serviced fossil fuel burning appliance should allow complete burning of the fuel and therefore is not a hazard. You should have all such appliances serviced at least once a year by a fully qualified Gas Safe registered engineer.

TYPICAL SOURCES OF CARBON MONOXIDE AROUND THE AVERAGE HOUSEHOLD ARE:

Room heaters; such as real flame fires, wood-burners, ranges; open coal, coke and wood fires, portable gas and paraffin heaters. Central heating boilers. Oil fired and gas central heating boilers, wood-burners and automated feeders for coke and coal.

Cookers and solid fuel ranges.

NOTE: Cooker hoods without flues will not remove CO.

Barbecues and chimneys used outside but close to the property

Petrol and diesel driven engines such as cars, motorbikes, lawn mowers, strimmers, rotovators, chain saws etc, especially when run up inside the garage or garden shed.

Cigarette, cigar and pipe smoke. Carbon monoxide from burning tobacco can build up over even a short time, particularly in a poorly ventilated property.

Blocked flues from fires, ranges and boilers. A partially blocked flue will cause a build up of unburned gases in the system and, if damaged by building movement or poor condition, could either severely affect complete burning or leak combustion gases into the property, particularly when they take air from the room to improve efficiency of exhaust.

Typical causes of carbon monoxide in the home are

Incorrect Installation of Equipment Always use a registered Gas Safe Installation Engineer.

Faulty Equipment; Cracked /blocked flues or cracked heat exchangers

Insufficient Ventilation for Complete Combustion. Where appliances take air for combustion from the room such as open wood and coal fires, portable gas or paraffin heaters or space-heating boilers, the room **MUST** have adequate ventilation to allow sufficient air for complete combustion. DO NOT block up room vents specifically provided for this purpose.

Appliances Competing for Air Supply Where there is more than one appliance taking air from a room ensure that there is an adequate supply. Consult your Gas Safe Engineer

Air tightness of the Property. This can happen if there is a lack of unobstructed ventilation in the presence of double glazing.

Holiday Accommodation. Take particular care when using holiday accommodation at home or abroad. Make sure you understand the type of appliances you are using and take note of the fuel being used. The 1137 Carbon Monoxide alarm is particularly suitable for this. Always take the handbook with you and read these instructions.

HAVING A WORKING CARBON MONOXIDE ALARM IN YOUR PROPERTY SHOULD NOT BE SEEN AS A REASON TO AVOID THE REGULAR SERVICING OF FUEL BURNING APPLIANCES.

IMPORTANT: This device is not suitable as a smoke, fire or combustible gas detector. It should not be regarded as a substitute for the proper servicing of fossil fuel burning appliances such as gas, oil, paraffin, bio-fuel, wood, coke, charcoal or coal fired boilers, room heaters and cookers etc, or their flues.

Deta Electrical Company Limited.

Kingsway House, Laporte Way, Luton, Bedfordshire, LU4 8RJ, United Kingdom.

Telephone: +44 (0)1582 544 500

Technical helpline: +44 (0)1582 544 548

DETA

BATTERY OPERATED

Carbon Monoxide Alarm Manual

1137



BS EN 50291-1:2010
License No. KM 573122



READ AND RETAIN THIS USER MANUAL

Firehawk CO7B