



LED Fire Rated Downlight

Description

Integrated LED fire rated downlight for residential and commercial applications

This Downlight is compact and versatile with a lens optimised to ensure even dispersion of flicker free light at a 38° beam angle.

Features

- Ideal solution for both residential and commercial applications
- CCT Switch on front of unit under bezel (3000K/4000K/5000K)
- IC rated - Building insulation can safely cover the luminaire
- Dimmable and optimised for use with Deta Universal Dimmers
- 30, 60 & 90 minute fire rated in timber joist floor construction – Building Regulations Part B compliant, gasket prevents air movement through fitting (BS 5250 Control of Condensation) and reduces passage of sound (Part E of Building Regs.)
- Interchangeable magnetic white bezel supplied as standard, Brushed Chrome (A4005) and Polished Chrome (A4006) bezels available as accessories
- Remote driver with loop-in/loop-out screwless terminal block for easy termination of T&E cables Loop in, loop out remote driver
- 3-year Guarantee

Dimensions & Weight

	Cut out	Diameter	Height	Weight
A4030	68-70mm	90mm	52mm	0.3kg

Contact your local authority for information concerning the correct disposal of your product.

Range

A4030	6W LED CCT Fire Rated Downlight
A4005	Brushed Chrome
A4006	Polished Chrome

Technical Specification

Voltage	220-240V
Frequency	50-60Hz
Operating Wattage	6W
LED Chip	XUYU
Power Factor	≤0.9
Colour Temperature	3000K Warm White 4000K Cool White 5000K Daylight White
Construction	Aluminium body
Luminous Flux	570lm
Beam Angle	38°
IP Rating	IP65
Dimmable	Yes
Light Source	Non-replaceable LED
Lifespan	50,000 Hours
Luminous Efficacy	95 lm/W
Standards	BS EN 60598-1