



Festoon Kits - 110V

Description

Briticent's Festoon Lighting Kit's are suitable for site lighting applications and are available with LED or GLS lamps. All are available with either BS or ES lampholders.

Features

- Suitable temporary lighting solution for both indoor and outdoor use
- Complete 22m kit including 10 x lamps and 10 x wire guards
- Available with either GLS or LED bulbs and lamp holders
- Lamp holder spacing every 2m
- 2m lead-in from plug to first lamp
- Arctic grade 2.5mm cable
- Replacement lamps and guards available separately
- 1-year warranty

Range

| SEFLLEDES | 10 x 8W E27 LED 22m LED Kit |
|-----------|-----------------------------|
| SEFLLEDBC | 10 x 8W B22 LED 22m LED Kit |
| SEFLKITES | 10 x 60W E27 22m GLS Kit |
| SEFLKITBC | 10 x 60W B22 22m GLS Kit |
| GLS60B | 60W B22 GLS Lamp |
| GLS60E | 60W E27 GLS Lamp |
| R1010 | 8W B22 LED Lamp |
| R1020 | 8W E27 LED Lamp |
| SEPC | Festoon Polycarbonate Guard |

Technical Specification

| Voltage | 110V | | |
|--------------------|--------------------------------|------------------|--|
| Frequency | 50-60Hz | ! | |
| Operating Wattage | 8W LED / 60W GLS | | |
| Power Factor | ≤0.9 | | |
| Colour Temperature | LED | 4000K Cool White | |
| | GLS | 2800K Warm White | |
| Construction | Polycarbonate | | |
| Luminous Flux | 700lm per Lamp | | |
| Beam Angle | 360° | | |
| IP Rating | IP44 | | |
| Light Source | Replaceable LED/GLS Lamps | | |
| Lifespan | 30,000 H | Hours | |
| Luminous Efficacy | 88lm/W | 1 | |
| Cable | 2.5mm ² Artic Grade | | |

Dimensions

| | Length | Cable |
|-----------|--------|--------------------|
| SEFLLEDES | 22m | 2.5mm ² |
| SEFLLEDBC | 22m | 2.5mm ² |
| SEFLKITES | 22m | 2.5mm ² |
| SEFLKITBC | 22m | 2.5mm ² |
| • | | |

Contact your local authority for information concerning the correct disposal of your product.