


Plateswitches



Description

This uniquely styled range has concealed screws behind a smooth frontplate with the Slimline profile.

This range of plateswitches do not have to be de-rated for fluorescent loads and can be used by controlling lighting, door releases and bells.

Features

- Unique slim profile with curved top and bottom edges
- All plate switches are x-rated and can be used for switching inductive or fluorescent loads with de-rating
- Frontplates supplied in protective polybag
- Concave rockers
- Only one size 4mm screwdriver needed
- Clear white markings
- Grey font engraving
- Terminals have large lead-ins
- 25-year guarantee

Range

10A 1 gang 2-way plate switch	8601
10A 2 gang 2-way plate switch	8602
10A 3 gang 3-way plate switch	8603
10A 4 gang 4-way plate switch	8604
10A intermediate plate switch	8606
10A 3 pole fan isolator switch	8607

Suffix finish with

White with white inserts	WHW
Chrome with white inserts	CHW

Technical Specification

Voltage rating	250Vac
Current Rating	10A
	X Rated
Contact gap	3mm

No user serviceable parts

Back Boxes

Minimum recommended depth

	Flush 25mm	Dry lining 35mm	Surface 25mm
1-3g	DB152	DB2540	V1220/E
4-6g	DB163	DB2541	V1223

Standards

- BS 60669-1:2000

Terminal Capacity

	2.5mm ²	4mm ²	6mm ²	10mm ²
L	5	4	2	1