



Vimark IP65 Integrated LED Fire Rated Downlights

Description

A range of low energy integrated LED fire rated downlights, dimmable and IP65 as standard

Features

- Compact profile enables installation within shallow ceiling voids
- Interchangeable twist and lock white bezel supplied as standard. Chrome and stainless-steel bezels available as accessories
- Fixing spring suitable for single or double thickness plasterboard
- Screwless terminal block on the LED driver for looping Twin and Earth cable
- Inline connector between driver and downlight reduces installation time
- Colour temperatures - 4000K and 3000K
- AmbiDim version provides a warmer lighting tone (3000K to 2200K) as light levels are reduced
- IC rated construction allows insulation to be laid directly over the top of the fitting
- Fire rating compliance for 30,60 and 90 minutes (Part B of Building Regs.)
- Gasket prevents air movement through fitting (BS 5250 Control of Condensation) and reduces passage of sound (Part E of Building Regs.)

Technical Specification

Voltage rating	240V AC 50 Hz
Power	6W
Lamp	Integrated LED
Lumens	550lm
IP rating	IP65
Fire rating	30, 60 and 90 mins.
Class	II (double insulated)
Dimmable	Yes

No user serviceable parts

Range

LED FR Downlight Fixed IP65 3000K	L1402WH3
LED FR Downlight Fixed IP65 4000K	L1402WH4
LED FR Downlight Fixed IP65 - AmbiDim 3000-2200K	L1421WH
Bezel Chrome	L1409CH
Bezel Stainless Steel	L1409SS

Dimensions

	Fixed	IP65
Cut out Ø	70	70
Min. Void depth	60	60
Bezel Ø	85	85

All dimensions in mm

Standards

BS EN 60598-1	Safety
BS 476-21	Fire rating
BS EN 140-3	Acoustic - airborne
BS EN 140-6	Acoustic - impact
BS 5250	Control of Condensation