



## Slimline Batten Range

### Description

The Slimline Batten range is available with or without a selectable CCT option. The CCT option is dimmable via an accessory remote which allows to control the colour temperature range from 3000K to 6000K

### Features

- Ideal solution for both home and office applications
- Suitable for surface and ceiling mounting
- Dimmable and CCT function via external remote (BR5410) available separately
- Fittings can be grouped and controlled simultaneously
- Up to four pairing groups per controller
- Memory function automatically stores last CCT and brightness level
- 20,000 lifetime operation hours
- 3-year Guarantee

### Technical Specification

Voltage	220V-240V	
Frequency	50-60Hz	
Colour Temperature	3000K Warm white 4000K Cool white 6000K Daylight white	
Construction	Aluminium body and Polycarbonate diffuser	
IP Rating	IP20	
Dimmable	Yes	
Light Source	Non-replaceable LED	
Lifespan	20,000hrs	
Luminous Flux	18W	1600lm
	36W	3200lm
	50W	4000lm
	72W	5760lm
Luminous Efficacy	80 lm/W	
Standards	BS EN	

No user serviceable parts

### Range

BR5412	18W 2ft CCT Batten
BR5414	36W 4ft CCT Batten
BR5415	50W 5ft CCT Batten
BR5416	72W 6ft CCT Batten

### Dimensions

	Length	Width	Height
BR5412	600mm	75mm	23.7mm
BR5414	1200mm	75mm	23.7mm
BR5415	1500mm	75mm	23.7mm
BR5416	1800mm	75mm	23.7mm

Contact your local authority for information concerning the correct disposal of your product.

### Remote

- On/off, dimming and CCT control options from remote
- Control operation up to 30m
- Four control channels allow for simultaneous control of up to:
  - 50 x 2ft battens
  - 25 x 4ft battens
  - 20 x 5ft battens
  - 16 x 6ft battens