



FBT4N

4 Hour Electronic Boost Timer and Fused Spur

Features

- Ideal for immersion heaters, room heaters, towel rails and lighting
- Replaces existing single gang connection unit or fixed appliance outlets
- Easy push button selection with clear LED output status
- Provides timed output protected by a BS1362 fuse switch

Technical Specification

Operating Voltage	230V AC
Frequency	50Hz
Installation Type	Flush Wall Box / Surface Mount Mattress Box
Earth Class Rating	Class II
Operating Temperature	0°C to 40°C
Ingress Protection Rating	IP20
Setting Type	Digital
Back Box Minimum Depth (mm)	25
Program Modes	Countdown
Standby Consumption	<0.7W
Number Of Channels	1
Switch Rating	13A Resistive, 1000W Incandescent/Halogen, 500W Fluorescent, 200W LED, 100W CFL
Shortest Switching Time	15 Minutes
Time Delay Range	¼ hour, ½ Hour, 1 Hour, 2 Hour or 4 Hour
Permanent ON Facility	No
Cable Entry(s)	Bottom Entry, Back Entry

Dimensions

Weight: 128g
 Height: 85 mm
 Width: 85 mm
 Depth: 42 mm
 Protruding Depth: 32 mm

Line Diagram(s)

