



## FST24

### 24 Hour Fused Spur Time Switch


#### Features

- Suitable for use with up to 3kW immersion heaters
- Red LED 'Mains ON' and green LED 'Output' indicators for easy viewing
- Permanent OFF and timed outputs available
- Easy view 24-hour digital clock/timer display
- Optional boost facility
- Automatic summer/wintertime changeover
- Self-cancelling override
- Programme advance and review options
- Integral memory back up battery retains programmes in event of power failure
- Ideal for replacing single gang connection unit or fixed appliance outlets
- Double pole switch for ease of control BS1362 fuse replaceable from front

#### Dimensions

Weight:	114 g
Height:	85 mm
Width:	85 mm
Depth:	43 mm
Protruding Depth:	30 mm

#### Line Diagram(s)



#### Technical Specification

Operating Voltage	230V AC
Frequency	50Hz
Installation Type	Flush Wall Box / Surface Mount Pattrass Box
Earth Class Rating	Class II
Operating Temperature	0°C to 40°C
Ingress Protection Rating	IP20
Setting Type	Digital
Battery Type	NiMH 1.2V 80mAh Rechargeable Battery (Non 672 Hours (28 Days)
Power Reserve	25
Back Box Minimum Depth (mm)	
Program Modes	24 Hour, 1 Hour/2Hour Boost
Switch Type	Double Pole (Isolation Switch)
Standby Consumption	<0.91W
Number Of Channels	1
Switch Rating	13A Resistive, 750W Incandescent/Halogen, 500W Fluorescent, 200W LED, 100W CFL
Shortest Switching Time	1 Minute
Programmable Slots	4 ON, 4 OFF
Permanent ON Facility	Yes
Cable Entry(s)	Bottom Entry, Back Entry
Body Construction	Polycarbonate
Product Colour	White
Accessories (Included)	Fittings