



FST24SL

Slim Line 24 Hour Fused Spur Time Switch

Features

- Suitable for use with up to 3kW immersion heaters
- Red LED 'Mains ON' and green LED 'Output' indicators for easy viewing
- Permanent OFF and timed outputs available
- Easy view 24 hour digital clock/timer display
- Optional boost facility
- Automatic summer/winter time changeover
- Self-cancelling override
- Programme advance and review options
- Integral memory back up battery retains programmes in event of power failure
- Ideal for replacing single gang connection unit or fixed appliance outlets (10mm spacer included)
- Single pole switch for ease of control BS1362 fuse replaceable from front

Dimensions

| | |
|-------------------|------|
| Weight: | 150g |
| Height: | 85mm |
| Width: | 85mm |
| Depth: | 35mm |
| Protruding Depth: | 10mm |

Technical Specification

| | |
|------------------------------------|--|
| Operating Voltage | 230V AC |
| Frequency | 50Hz |
| Installation Type | Flush Wall Box / Surface Mount Pattress Box |
| Earth Class Rating | Class II |
| Operating Temperature | 0°C to 40°C |
| Ingress Protection Rating | IP20 |
| Setting Type | Digital |
| Battery Type | NiMH 1.2V 80mAh Rechargeable Battery (Non-Replaceable) |
| Power Reserve | 672 Hours (28 Days) |
| Back Box Minimum Depth (mm) | 35 |
| Program Modes | 24 Hour, 1 Hour/2Hour Boost |
| Switch Type | Single Pole |
| Standby Consumption | <0.91W |
| Number Of Channels | 1 |
| Switch Rating | 13A Resistive, 750W Incandescent/Halogen, 500W Fluorescent, 200W LED, 100W CFL |
| Shortest Switching Time | 1 Minute |
| Programmable Slots | 4 ON, 4 OFF |
| Permanent ON Facility | Yes |
| Cable Entry(s) | Bottom Entry, Back Entry |
| Body Construction | Polycarbonate |
| Product Colour | White |
| Accessories (Included) | Fittings |