



IR10AB

Infra-Red Remote Control - for use with PIR Presence/Absence Detectors


Features

- Ceiling mount presence/absence detectors can be set up and adjusted without the use of ladders
- Adjustable light (LUX) and time ON settings at the touch of a button
- Easy to set by symbol recognition
- Extended lamp ON times available
- 5m (approx) transmission range
- 3V DC (CR2032 battery) factory fitted & replaceable

Dimensions

Weight: 32g
Height: 110mm
Width: 55mm
Depth: 8.2mm

Line Diagram(s)



Technical Specification

Operating Voltage	3V DC
Earth Class Rating	Class III
Operating Temperature	0°C to +45°C
Ingress Protection Rating	IP40
Setting Type	IR Remote
Battery Type	CR2032 3V (Replaceable)
Transmission Distance	up to 5m (Line of Sight)
Program Modes	Lux Adjustment, Time On Adjustment, Manual Override, Test Mode, Pulse Mode, Presence/Absence Mode
Push Buttons	Yes
Standby Consumption	<2.5uA
Shortest Switching Time	30 Seconds
ON Time Adjustment	30 Sec, 1 Min, 3 Min, 5 Min, 10 Min, 20 Min, 30 Min, 60 Min. User Adjustable
LUX Level	10, 50, 100, 300, 500, 1000, 2000. User Adjustable
Permanent ON Facility	Yes (10 Hours Max)
Multiple Unit Support	Yes
Body Construction	Plastic
Product Colour	Black
Accessories (Included)	CR2032 Battery