



TGBT4N

4 Hour Electronic Boost Timer


Features

- Automatic timer countdown selection for up to 4 hours.
- Typical applications such as immersion heaters, room heaters, towel rails and lighting.
- Fits a standard flush or surface mount BS wall box min. 25mm deep.

Dimensions

Weight: 113g
Height: 85mm
Width: 85mm
Depth: 31mm

Line Diagram(s)



Technical Specification

Operating Voltage	230V AC
Frequency	50Hz
Installation Type	Surface
Earth Class Rating	Class II
Operating Temperature	0°C to 45°C
Ingress Protection Rating	IP20
Setting Type	Button Press
Back Box Minimum Depth (mm)	25
Push Buttons	Yes (Boost Button)
Mounting Hole Centres (mm)	60
Standby Consumption	<1W
Number Of Channels	1
Switch Rating	13A Resistive, 100W LED, 1000W Halogen, 500W Fluorescent
Shortest Switching Time	15 Minutes
Time Delay Range	15 Minutes to 4 Hours (¼ Hour, ½ Hour, 1 Hour, 2 Hours and 4 Hours)
Permanent ON Facility	No
Multiple Unit Support	No
Body Construction	Polycarbonate
Product Colour	White
Accessories (Included)	Screws