



## ZV700N

### Digital Light Switch with Optional Dusk Start

#### Features

- 6 different time periods (5 day plus 2 day or 7 day programming) displayed on an easy-view blue illuminated screen
- Auto mode: The light output will be controlled by the programmed times
- Photocell mode: The light output will only come on when the light level drops, if it is within a programmed times
- Random mode: On a random basis, it can change the ON/OFF times programmed by up to 30 minutes earlier, or later than programmed
- Manual mode: The light output is controlled by the Adv button, not the programmed times
- Automatic summer/winter time changeover
- Fits a standard flush or surface mount BS wall box min 25mm
- 2-wire no neutral required
- Internal battery powers the switches controls, therefore the lamps will not flicker when a minimum load is connected
- Note: FLA01 strip light adaptor or the ZV900 load controller may be required in certain installations

#### Dimensions

Weight: 180g  
 Height: 85mm  
 Width: 85mm  
 Depth: 35mm  
 Protruding Depth: 27mm

#### Technical Specification

Operating Voltage	230V AC
Frequency	50Hz
Installation Type	Flush
Earth Class Rating	Class II
Operating Temperature	0°C to 40°C
Ingress Protection Rating	IP20
Connection	2-Wire
Battery Type	PP3 9V
Power Reserve	Up to 720 Hours
Back Box Minimum Depth (mm)	25
Program Modes	24 Hour, 7 Day, Permanent ON/OFF, Photocell, Random or Timed
Switch Type	Two Way (With Manual Rocker Switch)
Mounting Hole Centres (mm)	60.3
Standby Consumption	<1W
Switch Rating	0 - 50W LED Extendable up to 200W With ZV900, 40 - 400W Filament, 11 - 150W Low Energy (Min bulb size 11W), 18 - 76W Fluorescent
Shortest Switching Time	1 Minute
Programmable Slots	6 ON, 6 OFF
Permanent ON Facility	Yes
Multiple Unit Support	No
Cable Entry(s)	Back Entry
Body Construction	Polycarbonate
Product Colour	White
Accessories (Included)	Fixing Screws