

# Product datasheet

Specifications

## LINERGY FM 4P DIS.BLOCK 200A 24M 54HOLES



04014

⚠ Discontinued on: 5 Apr 2023

EAN Code: 3303430040149

⚠ Discontinued

### Main

Range	Linergy
Range of product	Linergy
Product or component type	Device feeder
Product name	Linergy FM
Range compatibility	Prisma Prisma G enclosure Prisma Prisma P enclosure Prisma Prisma PH enclosure
Product compatibility	Spacial enclosures
IP degree of protection	IPxx B

### Complementary

Mounting support	DIN rail Plain backplate Slotted backplate
Installed device	modular device
Poles description	3P + N
[Ue] rated operational voltage	690 V AC
[Ui] rated insulation voltage	750 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	8 kV
[Ie] rated operational current	200 A
[In] rated current	200 A at 40 °C
[Ipk] rated peak withstand current	20 kA
I <sup>t</sup> on activation	6700000 A <sup>2</sup> .s
Connections - terminals	Supply: crimped lug50 mm <sup>2</sup> Supply: flexible bars, 20 x 3 mm Distribution: quick-connect terminal strips (phase) , 12 x 4...10 mm <sup>2</sup> (flexible) Distribution: quick-connect terminal strips (phase) , 12 x 4...10 mm <sup>2</sup> (rigid) Distribution: quick-connect terminal strips (neutral) , 18 x 4...10 mm <sup>2</sup> (flexible) Distribution: quick-connect terminal strips (neutral) , 18 x 4...10 mm <sup>2</sup> (rigid)
9 mm pitches	48
Total number of 18 mm modules	24
Net weight	1.6 kg
Colour	Anthracite grey (RAL 7016)

### Environment

---

<b>Standards</b>	IEC 61439-1, inside Prisma IEC 61439-2, inside Prisma IEC 60947-7-1
------------------	---

---

<b>Product certifications</b>	ASEFA
-------------------------------	-------

---

## Packing Units

---

<b>Unit Type of Package 1</b>	PCE
-------------------------------	-----

---

<b>Number of Units in Package 1</b>	1
-------------------------------------	---

---

<b>Package 1 Height</b>	6.8 cm
-------------------------	--------

---

<b>Package 1 Width</b>	8 cm
------------------------	------

---

<b>Package 1 Length</b>	44.6 cm
-------------------------	---------

---

<b>Package 1 Weight</b>	1.595 kg
-------------------------	----------

---

## Contractual warranty

---

<b>Warranty</b>	18 months
-----------------	-----------

---

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

## Use Better

### Materials and Substances

[EU RoHS Directive](#)

Compliant

Halogen-free status

Halogen free plastic parts product

PVC free

Yes

Silicone-free

Yes


## Use Again

### Repack and remanufacture

Take-back

No

WEEE Label

 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins