

Product datasheet

Specifications



mini Kaedra - for modular device - 1 openings - 12 modules - 2 terminal blocks

Local distributor code:

385332053

13444

EAN Code: 3303430134442

Main

Range	Mureva
Product name	Mureva Enclosure
Product or component type	Weatherproof enclosure
enclosure type	Mini enclosure for modular device
Mounting plate description	Without mounting plate

Complementary

Enclosure mounting	Surface
9 mm pitches	24
Number of 18 mm modules per row	12
Total number of 18 mm modules	12
Number of horizontal rows	1
Electrical insulation class	Class II Double insulation
Provided equipment	1 marking kit 2 terminal block 8 holes
Type of front cover	Transparent
Power dissipation in W	19 W
[In] rated current	63 A
Type of rail	DIN
Number of pre-cutouts PG ISO	7
Number of terminal blocks	2 earth / neutral (screw connection) with 8 outgoers
Distribution block outgoers	8 x 10 mm ² 8 x 16 mm ²
Locking options description	Optional keylock
Enclosure material	Self-extinguishing polymer
Width	267 mm
Height	200 mm
Depth	112 mm
Internal depth	56 mm
Colour	Door: transparent green Enclosure: light grey (RAL 7035)

Environment

Standards	IEC 60670-1 IEC 60670-24 EN 50262 IEC 60695-2-1
Fire resistance	650 °C conforming to IEC 60695-2-1
IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK09 conforming to EN 50102
Environmental characteristics (UV)	UV resistant: class 3 conforming to ISO 4582:2010 Ultraviolet degradation test conforming to ISO 4892-2:2013
Overvoltage category	II
Ambient air temperature for operation	-25...60 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	11.000 cm
Package 1 Width	20.000 cm
Package 1 Length	26.500 cm
Package 1 Weight	942.000 g
Unit Type of Package 2	CAR
Number of Units in Package 2	4
Package 2 Height	22.000 cm
Package 2 Width	35.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	4.168 kg
Unit Type of Package 3	P12
Number of Units in Package 3	96
Package 3 Height	80.000 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	104.432 kg

Logistical informations

Country of origin	IT
-------------------	----

Contractual warranty

Warranty	18 months
----------	-----------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Total lifecycle Carbon footprint	6
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances

Average percentage of recycled plastic content	24 %
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
SCIP Number	5305d5d6-3783-4b3d-abd0-61fa4a6023d7
REACH Regulation	REACH Declaration
Halogen-free status	Halogen free product

Use Again

Repack and remanufacture

End of life manual availability	No need of specific recycling operations
Take-back	No