

Product datasheet

Specifications



auxiliary contact - 1 OC + 1 SD - 6 A - 220..240 V - for NG125

Local distributor code:

382141056

19072

⚠ Discontinued on: 14 Jul 2023

EAN Code: 3303430190721

⚠ To be discontinued

Main

range of product	Acti9
Product or component type	OC and fault contact
Device short name	OF and SD
Signal contacts composition	2 C/O
[In] rated current	0.1...3 A at 415 V, AC 50/60 Hz 0.1...6 A at <= 240 V, AC 50/60 Hz 0.1...1 A at 130 V, DC 0.1...3 A at <= 48 V, DC
9 mm pitches	1
Standards	EN/IEC 60947-5-1

Complementary

Range compatibility	Acti9 NG125NA Acti9 NG125LMA Acti9 NG125
[Ui] rated insulation voltage	690 V AC 50/60 Hz conforming to EN/IEC 60947-5-1
[Uimp] rated impulse withstand voltage	8 kV conforming to EN/IEC 60947-5-1
Mounting mode	Fixed
Mounting support	DIN rail
Height	102.8 mm
Width	9 mm
Depth	75.5 mm
Electrical durability	10000 cycles conforming to EN/IEC 60947-5-1
Connections - terminals	Plate terminal1 cable(s) 0.5...2.5 mm ² - rigid Plate terminal1 cable(s) 0.5...1.5 mm ² - flexible Plate terminal1 cable(s) 0.5...1.5 mm ² - flexible with ferrule Plate terminal2 cable(s) 2.5 mm ² - rigid Plate terminal2 cable(s) 2.5 mm ² - flexible Plate terminal2 cable(s) 1.5 mm ² - flexible with ferrule
Wire stripping length	10 mm
Tightening torque	1 N.m

Environment

Pollution degree	3 conforming to EN/IEC 60947-5-1
Tropicalisation	2 conforming to EN/IEC 60947-5-1

Ambient air temperature for operation	-25...60 °C
Ambient air temperature for storage	-40...85 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.5 cm
Package 1 Width	8 cm
Package 1 Length	10.5 cm
Package 1 Weight	67 g
Unit Type of Package 2	BB1
Number of Units in Package 2	9
Package 2 Height	8.5 cm
Package 2 Width	11.5 cm
Package 2 Length	23.5 cm
Package 2 Weight	660 g
Unit Type of Package 3	S03
Number of Units in Package 3	81
Package 3 Height	30 cm
Package 3 Width	30 cm
Package 3 Length	40 cm
Package 3 Weight	6.336 kg

Contractual warranty

Warranty	18 months
----------	-----------


Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.



[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

 Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant
REACH Regulation	REACH Declaration

Use Again

 Repack and remanufacture	
End of life manual availability	No need of specific recycling operations
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins