

# Product datasheet

Specifications



## UA controller, Transferpack, 220 VAC to 240 VAC 50/60Hz

Local distributor code:

382193224

29378

EAN Code: 3303430293781

### Main

Range of product	Compact NS630b...1600 MasterPact NT MasterPact NW Compact NS100...630
Product name	UA
Device short name	UA
Product or component type	Control unit

### Complementary

[Us] rated supply voltage	220...240 V AC at 50/60 Hz
Operating mode	Forced operation on replacement source Stop (both normal and replacement source off) Automatic operation Forced operation on normal source
Interlocked device	MasterPact NW Compact NS100...630 Compact NS630b...1600 MasterPact NT
Selection modes	Circuit breaker on R Circuit breaker on N
Genset exerciser	Startup control Adjustable delayed shutdown
Complementary function	Selection of type of normal source (single-phase or three-phase) Setting of maximum startup time for the replacement source Voluntary transfer to replacement source (e.g. energy management commands) Forced normal source if replacement source not operational during peak-tariff Additional contact: transfer to replacement source only if contact is closed
Local signalling	Fault trip On Off
Test function	By pressing the test button on the front of the controller
Input type	Contacts customer voluntary order to transfer to source R
Output type	Contacts customer: indication of operation in automatic or stop mode
[Ith] conventional free air thermal current	8 A
[Ie] rated operational current	AC-12: 4 A AC 440 V AC-12: 5 A AC 380/415 V DC-13: 2 A 24 V

### Environment

Standards	IEC 947-5-1
-----------	-------------

---

<b>IP degree of protection</b>	IP20 connectors: conforming to EN 60529 IP40 front: conforming to EN 60529 IP30 side: conforming to EN 60529
--------------------------------	--

---

<b>IK degree of protection</b>	Front: IK07 conforming to EN 50102
--------------------------------	------------------------------------

## Packing Units

---

<b>Unit Type of Package 1</b>	PCE
-------------------------------	-----

---

<b>Number of Units in Package 1</b>	1
-------------------------------------	---

---

<b>Package 1 Height</b>	15.6 cm
-------------------------	---------

---

<b>Package 1 Width</b>	15.6 cm
------------------------	---------

---

<b>Package 1 Length</b>	18.0 cm
-------------------------	---------

---

<b>Package 1 Weight</b>	1.586 kg
-------------------------	----------

---

<b>Unit Type of Package 2</b>	S04
-------------------------------	-----

---

<b>Number of Units in Package 2</b>	6
-------------------------------------	---

---

<b>Package 2 Height</b>	30.0 cm
-------------------------	---------

---

<b>Package 2 Width</b>	40.0 cm
------------------------	---------

---

<b>Package 2 Length</b>	60.0 cm
-------------------------	---------

---

<b>Package 2 Weight</b>	10.282 kg
-------------------------	-----------

## Logistical informations

---

<b>Country of origin</b>	FR
--------------------------	----

## Contractual warranty

---

<b>Warranty</b>	18 months
-----------------	-----------


## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Better

 <b>Materials and Substances</b>	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
<a href="#">EU RoHS Directive</a>	Compliant with Exemptions
SCIP Number	Acf791c5-78f0-4053-a7c8-a79590f1d0a3

### Use Again

 <b>Repack and remanufacture</b>	
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative

---

