

Product datasheet

Specifications



voltage release - iMX+OF - tripping unit - 220..415 VAC

Local distributor code:
396737317

A9A26946

EAN Code: 3606480088049

Main

range of product	Acti9
Product or component type	Shunt trip release with OC contact
Device short name	iMX+OF
Signal contacts composition	1 C/O
[In] rated current	AC-12 3 A at 415 V, AC 50 Hz AC-12 6 A at 100 V, AC 50 Hz AC-12 6 A at 230 V, AC 50 Hz DC-12 1 A at 110 V, DC DC-12 1 A at 130 V, DC
[Uc] control circuit voltage	100...415 V AC 50/60 Hz 110...130 V DC
9 mm pitches	2

Complementary

Range compatibility	Acti9 iC60H RCBO Acti9 iC60H RCBO PoN Acti9 iC60H2 RCBO Acti9 iC60N RCBO Acti9 iKQE RCBO
Local signalling	Action indicator
Mounting mode	Clip-on
Mounting support	DIN rail
Comb busbar and distribution block compatibility	Top: YES
Width	18 mm
Colour	White
Connections - terminals	Clamp terminal - 2 cable(s) 2.5 mm ² - flexible with cable end Clamp terminal - 1 cable(s) 6 mm ² - rigid Clamp terminal - 2 cable(s) 2.5 mm ² - rigid Clamp terminal - 1 cable(s) 4 mm ² - flexible
Tightening torque	1 N.m

Environment

Standards	EN/IEC 60947-1 EN/IEC 60947-5-1
Tropicalisation	2 conforming to EN/IEC 60947-5-1
Relative humidity	95 % at 55 °C
Ambient air temperature for operation	-35...70 °C

Ambient air temperature for storage	-40...85 °C
-------------------------------------	-------------

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
------------------------------	---

Package 1 Height	3 cm
------------------	------

Package 1 Width	8 cm
-----------------	------

Package 1 Length	9.5 cm
------------------	--------

Package 1 Weight	78 g
------------------	------

Unit Type of Package 2	BB1
------------------------	-----

Number of Units in Package 2	8
------------------------------	---

Package 2 Height	9 cm
------------------	------

Package 2 Width	10 cm
-----------------	-------

Package 2 Length	27 cm
------------------	-------

Package 2 Weight	678 g
------------------	-------

Unit Type of Package 3	S03
------------------------	-----

Number of Units in Package 3	72
------------------------------	----

Package 3 Height	30 cm
------------------	-------

Package 3 Width	30 cm
-----------------	-------

Package 3 Length	40 cm
------------------	-------

Package 3 Weight	6.65 kg
------------------	---------

Logistical informations

Country of origin	BE
-------------------	----

Contractual warranty

Warranty	18 months
----------	-----------



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Total lifecycle Carbon footprint	490
----------------------------------	-----

Use Better

Materials and Substances

Packaging made with recycled cardboard	No
--	----

Packaging without single use plastic	Yes
--------------------------------------	-----

EU RoHS Directive	Compliant
-----------------------------------	-----------

REACH Regulation	REACH Declaration
------------------	-----------------------------------

Use Again

Repack and remanufacture

Recyclability potential, in %	0
-------------------------------	---

Take-back	No
-----------	----

WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
------------	---