

Product datasheet

Specifications



iCT 63A 4NC 220...240V 50Hz contactor

Local distributor code:
396892841

A9C20867

EAN Code: 3606480375163

Main

| | |
|--------------------------------|--------------------------|
| range of product | Acti9 |
| Product name | Acti9 iCT |
| Product or component type | Contacteur |
| Device short name | iCT |
| Device application | Motor-heating-lighting |
| Poles | 4P |
| [Ie] rated operational current | 63 A AC-7A 20 A AC-7B |
| Pole contact composition | 4 NC |
| Network type | AC |
| control type | Remote control |
| [Uc] control circuit voltage | 220...240 V AC 50 Hz |

Complementary

| | |
|--|------------------------------|
| Network frequency | 50 Hz |
| [Ue] rated operational voltage | 400 V AC 50 Hz |
| Maximum power | 2.1 W at 400 V AC |
| [Ui] rated insulation voltage | 500 V AC 50/60 Hz |
| [Uimp] rated impulse withstand voltage | 4 kV |
| Control signal type | Maintained |
| Switching frequency | 100 switching operations/day |
| Local signalling | Action indicator |
| Hold-in power consumption in VA | 6.5 VA |
| inrush power in VA | 53 VA |
| Mounting mode | Clip-on |
| Mounting support | 35 mm symmetrical DIN rail |
| 9 mm pitches | 6 |
| Height | 85 mm |
| Width | 54 mm |
| Depth | 60 mm |
| Colour | White |

| | |
|--------------------------------|--|
| Mechanical durability | 1000000 cycles |
| Electrical durability | 100000 cycles IEC/EN 61095 63 A 50 Hz AC-7A 30000 cycles IEC/EN 61095 20 A 50 Hz AC-7B 30000 cycles IEC/EN 61095 50 Hz AC-7C 100000 cycles EN/IEC 60947-4-1 50 Hz AC-1 30000 cycles EN/IEC 60947-4-1 50 Hz AC-3 30000 cycles EN/IEC 60947-4-1 50 Hz AC-5a 30000 cycles EN/IEC 60947-4-1 50 Hz AC-5b |
| Connections - terminals | Control circuit: tunnel type terminals2 cable(s) 1.5 mm ² rigid Control circuit: tunnel type terminals1 cable(s) 1.5...2.5 mm ² rigid Power circuit: tunnel type terminals1 cable(s) 6...16 mm ² flexible Power circuit: tunnel type terminals1 cable(s) 6...25 mm ² rigid Control circuit: tunnel type terminals2 cable(s) 1.5...2.5 mm ² flexible |
| Tightening torque | Control circuit: 0.8 N.m Power circuit: 3.5 N.m |
| Product compatibility | IACtP IACtS IACtC IACtE |
| Compatibility code | ICT |
| Market segment | Small commercial Residential |

Environment

| | |
|--|--|
| Standards | IEC/EN 61095 |
| Noise level | 30 dB |
| IP degree of protection | IP20 |
| Pollution degree | 2 |
| Tropicalisation | 2 conforming to EN 60947-4-1 2 conforming to EN 61095 2 conforming to IEC 1095 |
| Relative humidity | 95 % at 55 °C |
| Operating altitude | 2000 m |
| Ambient air temperature for operation | -5...60 °C |
| Ambient air temperature for storage | -40...70 °C |

Packing Units

| | |
|-------------------------------------|-----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 5.800 cm |
| Package 1 Width | 11.000 cm |
| Package 1 Length | 12.100 cm |
| Package 1 Weight | 359.000 g |
| Unit Type of Package 2 | BB1 |
| Number of Units in Package 2 | 4 |
| Package 2 Height | 11.500 cm |
| Package 2 Width | 12.500 cm |
| Package 2 Length | 25.200 cm |
| Package 2 Weight | 1.513 kg |

| | |
|-------------------------------------|-----------|
| Unit Type of Package 3 | S03 |
| Number of Units in Package 3 | 24 |
| Package 3 Height | 30.000 cm |
| Package 3 Width | 30.000 cm |
| Package 3 Length | 40.000 cm |
| Package 3 Weight | 9.550 kg |

Logistical informations

Country of origin FR

Contractual warranty

Warranty 18 months



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Total lifecycle Carbon footprint 581

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard No

Packaging without single use plastic No

[EU RoHS Directive](#) Compliant

SCIP Number 6763a476-30bc-4d05-a4bb-93f8d65c3771

REACH Regulation [REACH Declaration](#)

Halogen-free status Product contains halogen above thresholds

Use Again

Repack and remanufacture

End of life manual availability No need of specific recycling operations

Take-back No

WEEE Label  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins