

Product datasheet

Specifications



TeSys K - Time delay auxiliary contact block - 1 C/O - 24...48 V - 1...30s

Local distributor code:
23052983

LA2KT2E

EAN Code: 3389110230048

Main

Range	TeSys
Product name	TeSys K
Product or component type	Time delay auxiliary contact block
Device short name	LA1
Range compatibility	TeSys K LC1K TeSys K CA2K TeSys K CA3K TeSys K CA4K
Mounting location	Front
Pole contact composition	1 C/O
Contacts operation	Time delay
Timer type	On delay
Time delay range	1...30 s
[Ue] rated operational voltage	24...48 V AC/DC for control circuit 240 V AC for signalling circuit
Rated operational voltage limits	0.85...1.1 U _c
[I _{th}] conventional free air thermal current	2 A for signalling circuit
Standards	EN/IEC 60947-5-1
Product certifications	CE UKCA

Complementary

Insulation resistance	> 10 MΩ
Connections - terminals	Slip-on terminals
Reset time	1.5 s during time delay 0.5 s after time delay
Height	27 mm
Width	38 mm
Depth	38 mm
Net weight	0.04 kg

Environment

Environmental characteristic	Normal environment
IP degree of protection	IP20 conforming to IEC 60529

Protective treatment	TC conforming to IEC 60068
----------------------	----------------------------

Ambient air temperature for operation	-10...60 °C
---------------------------------------	-------------

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
------------------------------	---

Package 1 Height	5.000 cm
------------------	----------

Package 1 Width	4.800 cm
-----------------	----------

Package 1 Length	4.800 cm
------------------	----------

Package 1 Weight	40.000 g
------------------	----------

Unit Type of Package 2	S02
------------------------	-----

Number of Units in Package 2	70
------------------------------	----

Package 2 Height	15.000 cm
------------------	-----------

Package 2 Width	30.000 cm
-----------------	-----------

Package 2 Length	40.000 cm
------------------	-----------

Package 2 Weight	3.110 kg
------------------	----------

Logistical informations

Country of origin	TN
-------------------	----

Contractual warranty

Warranty	18 months
----------	-----------



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Total lifecycle Carbon footprint 4

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard Yes

Packaging without single use plastic Yes

[EU RoHS Directive](#) Compliant with Exemptions

SCIP Number 8a21c0d1-be95-4e83-b703-1e8075e942f8

REACH Regulation [REACH Declaration](#)


Use Again

Repack and remanufacture

Recyclability potential, in % 43

End of life manual availability No need of specific recycling operations

Take-back No

WEEE Label  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Technical Illustration

Assembly's dimensions

