

# Product datasheet

Specifications



## TeSys LC1D.K capacitor duty contactor - 3P - 25 kVAR - 415 V - 230 V AC coil

LC1DMKP7

EAN Code: 3606480401855

### Main

<b>Range</b>	TeSys TeSys Deca
<b>Product name</b>	TeSys LC1D.K TeSys Deca
<b>Product or component type</b>	Capacitor duty contactor
<b>Device short name</b>	LC1DMK
<b>Device application</b>	Control
<b>Contactors application</b>	Power factor correction
<b>Utilisation category</b>	AC-6b
<b>Poles description</b>	3P
<b>power pole contact composition</b>	3 NO
<b>Device location in system</b>	Line interruption Inside delta interruption
<b>[Ue] rated operational voltage</b>	Power circuit: 690 V AC 50/60 Hz
<b>Reactive power rating</b>	14 kvar at 230 V AC 50 Hz 60 °C 25 kvar at 400 V AC 50 Hz 60 °C 27 kvar at 440 V AC 50 Hz 60 °C 42 kvar at 690 V AC 50 Hz 60 °C
<b>Control circuit type</b>	AC at 50/60 Hz
<b>[Uc] control circuit voltage</b>	230 V AC 50/60 Hz
<b>Auxiliary contact composition</b>	1 NO + 2 NC instantaneous
<b>Electrical durability</b>	300000 cycles at Ue 400 V 200000 cycles at Ue 690 V
<b>Mounting support</b>	DIN rail Plate
<b>Standards</b>	EN/IEC 60947-1 EN/IEC 60947-4-1 IEC 60335-1
<b>Product certifications</b>	IECEE CB Scheme UKCA

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

<b>Connections - terminals</b>	Control circuit: screw clamp terminals 1 1...4 mm <sup>2</sup> - cable stiffness: solid Control circuit: screw clamp terminals 2 1...4 mm <sup>2</sup> - cable stiffness: solid Control circuit: screw clamp terminals 1 1...4 mm <sup>2</sup> - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 2 1...4 mm <sup>2</sup> - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 1 1...4 mm <sup>2</sup> - cable stiffness: flexible with cable end Control circuit: screw clamp terminals 2 1...2.5 mm <sup>2</sup> - cable stiffness: flexible with cable end Power circuit: screw clamp terminals 1 2.5...16 mm <sup>2</sup> - cable stiffness: solid Power circuit: screw clamp terminals 2 2.5...6 mm <sup>2</sup> - cable stiffness: solid Power circuit: screw clamp terminals 1 1.5...10 mm <sup>2</sup> - cable stiffness: flexible without cable end Power circuit: screw clamp terminals 2 1.5...6 mm <sup>2</sup> - cable stiffness: flexible without cable end Power circuit: screw clamp terminals 1 1...10 mm <sup>2</sup> - cable stiffness: flexible with cable end Power circuit: screw clamp terminals 2 1...4 mm <sup>2</sup> - cable stiffness: flexible with cable end
--------------------------------	---

<b>Tightening torque</b>	Control circuit: 1.7 N.m - on screw clamp terminals Power circuit: 2.5 N.m - on screw clamp terminals
--------------------------	--

<b>Maximum operating rate</b>	240 cyc/h
-------------------------------	-----------

## Complementary

<b>Auxiliary contacts type</b>	type mechanically linked 1 NO + 2 NC conforming to IEC 60947-5-1
--------------------------------	--

## Environment

<b>IP degree of protection</b>	IP20 front face conforming to IEC 60529
--------------------------------	---

<b>Ambient air temperature for operation</b>	-5...60 °C
--	------------

<b>Ambient air temperature for storage</b>	-60...80 °C
--	-------------

<b>Operating altitude</b>	0...3000 m
---------------------------	------------

<b>Height</b>	125 mm
---------------	--------

<b>Width</b>	45 mm
--------------	-------

<b>Depth</b>	127 mm
--------------	--------

<b>Net weight</b>	0.63 kg
-------------------	---------

## Packing Units

<b>Unit Type of Package 1</b>	PCE
-------------------------------	-----

<b>Number of Units in Package 1</b>	1
-------------------------------------	---

<b>Package 1 Height</b>	6.700 cm
-------------------------	----------

<b>Package 1 Width</b>	19.500 cm
------------------------	-----------

<b>Package 1 Length</b>	22.700 cm
-------------------------	-----------

<b>Package 1 Weight</b>	611.000 g
-------------------------	-----------

<b>Unit Type of Package 2</b>	S03
-------------------------------	-----

<b>Number of Units in Package 2</b>	6
-------------------------------------	---

<b>Package 2 Height</b>	30.000 cm
-------------------------	-----------

<b>Package 2 Width</b>	30.000 cm
------------------------	-----------

<b>Package 2 Length</b>	40.000 cm
-------------------------	-----------

<b>Package 2 Weight</b>	4.083 kg
-------------------------	----------

<b>Unit Type of Package 3</b>	P06
-------------------------------	-----

---

<b>Number of Units in Package 3</b>	48
<b>Package 3 Height</b>	75.000 cm
<b>Package 3 Width</b>	60.000 cm
<b>Package 3 Length</b>	80.000 cm
<b>Package 3 Weight</b>	43.532 kg

---

## Logistical informations

---

<b>Country of origin</b>	FR
--------------------------	----

## Contractual warranty

---

<b>Warranty</b>	18 months
-----------------	-----------



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Total lifecycle Carbon footprint 1

Environmental Disclosure [Product Environmental Profile](#)

### Use Better

#### Materials and Substances

Packaging made with recycled cardboard Yes

Packaging without single use plastic Yes

[EU RoHS Directive](#) Compliant

REACH Regulation [REACH Declaration](#)

### Use Again

#### Repack and remanufacture

Recyclability potential, in % 67

End of life manual availability No need of specific recycling operations

Take-back No

WEEE Label  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Technical Illustration

Assembly's dimensions

---

