

Product datasheet

Specifications



undervoltage release (spring) MN - 208...240 V AC 60Hz - 220...240 50Hz

LV426804

EAN Code: 3606485412818

Main

Range	ComPact
Range of product	ComPacT NSXm
Device short name	MN
Product or component type	Voltage release
Device application	Control
Voltage release type	Opening coil Undervoltage release
Control type	Standard
[Uc] control circuit voltage	220...240 V AC 50 Hz 208...240 V AC 60 Hz
Range compatibility	ComPact ComPacT NSXm ComPact ComPact NSXm PowerPact PowerPact B

Complementary

Operating threshold	0.35...0.7 x Un opening 0.85 x Un closing
Response time	< 50 ms
Auxiliary connection terminal	Spring

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.500 cm
Package 1 Width	6.000 cm
Package 1 Length	8.500 cm
Package 1 Weight	60.800 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	9.000 cm
Package 2 Width	13.000 cm
Package 2 Length	18.500 cm
Package 2 Weight	653.600 g
Unit Type of Package 3	S03

Number of Units in Package 3	40
Package 3 Height	30.000 cm
Package 3 Width	30.000 cm
Package 3 Length	40.000 cm
Package 3 Weight	2.880 kg

Logistical informations

Country of origin	FR
--------------------------	----

Contractual warranty

Warranty	18 months
-----------------	-----------



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Total lifecycle Carbon footprint 252

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard Yes

Packaging without single use plastic Yes

[EU RoHS Directive](#) Compliant with Exemptions

SCIP Number 75582d60-9779-4641-a03b-18e996230a58

REACH Regulation [REACH Declaration](#)

Halogen-free status Product contains halogen above thresholds

Silicone-free No

Use Again

Repack and remanufacture

Recyclability potential, in % 32

End of life manual availability [End of Life Information](#)

Take-back No

WEEE Label  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins