

Product datasheet

Specifications



standard motor mechanism module MT100/160, ComPact NSX100/160, 110/130 VAC 50/60 Hz

Local distributor code:

391352917

LV429433

EAN Code: 3606480019999

Main

Device short name	MT250
Product or component type	Motor mechanism
Device application	Automatic spring charging
Range compatibility	ComPacT NSX100 ComPacT NSX160 ComPacT NSX100 DC ComPacT NSX160 DC
Control type	Standard
[Uc] control circuit voltage	110...130 V AC 50/60 Hz
circuit breaker mounting mode	Fixed
circuit breaker frame rated current	100 A 160 A

Complementary

Control signal type	Maintained Impulse
circuit breaker response time	< 700 ms open < 80 ms closed
Maximum operating frequency	4 per minute
Maximum power consumption in VA	500 VA closing 500 VA opening
Provided equipment	SDE adaptor
Locking options description	Padlocking in OFF position 1 to 3 padlocks Ø 5 to Ø 8

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	12 cm
Package 1 Width	10.5 cm
Package 1 Length	17.3 cm
Package 1 Weight	1.386 kg
Unit Type of Package 2	S04
Number of Units in Package 2	15
Package 2 Height	30 cm

Package 2 Width 40 cm

Package 2 Length 60 cm

Package 2 Weight 21.661 kg

Logistical informations

Country of origin IT

Contractual warranty

Warranty 18 months

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Total lifecycle Carbon footprint 14

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard Yes

Packaging without single use plastic No

[EU RoHS Directive](#) Compliant with Exemptions

SCIP Number A3dc0f23-906d-490a-acce-c58e25990143

REACH Regulation [REACH Declaration](#)

Halogen-free status Product contains halogen above thresholds

Use Again

Repack and remanufacture

Recyclability potential, in % 73

End of life manual availability [End of Life Information](#)

Take-back No

WEEE Label  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins