


# Product datasheet

Specifications



## current transformer module with voltage output, ComPact NSX250, 250 A rating, 3 poles

Local distributor code:

391355684

LV431569

EAN Code: 3606480020797

### Main

|                           |                              |
|---------------------------|------------------------------|
| Device short name         | CT module and voltage output |
| Product or component type | Current transformer          |
| Device application        | Control                      |
| Range compatibility       | ComPact ComPact NSX250       |
| Poles description         | 3P                           |
| [In] rated current        | 250 A                        |
| Current transformer ratio | 250/5 A                      |
| Power consumption in VA   | 1.1 VA                       |
| Accuracy class            | Class 1                      |

### Complementary

|                                |                                     |
|--------------------------------|-------------------------------------|
| [Ue] rated operational voltage | 530 V                               |
| Network type                   | AC                                  |
| Network frequency              | 50/60 Hz                            |
| Auxiliary connection terminal  | Cable connector 2.5 mm <sup>2</sup> |

### Environment

|                                   |                              |
|-----------------------------------|------------------------------|
| Electrical shock protection class | Class II                     |
| IP degree of protection           | IP40 conforming to IEC 60529 |
| IK degree of protection           | IK04 conforming to IEC 62262 |

### Packing Units

|                              |         |
|------------------------------|---------|
| Unit Type of Package 1       | PCE     |
| Number of Units in Package 1 | 1       |
| Package 1 Height             | 13.5 cm |
| Package 1 Width              | 14.0 cm |
| Package 1 Length             | 17.5 cm |
| Package 1 Weight             | 991.0 g |
| Unit Type of Package 2       | S03     |
| Number of Units in Package 2 | 4       |
| Package 2 Height             | 30.0 cm |
| Package 2 Width              | 30.0 cm |

---

|                  |         |
|------------------|---------|
| Package 2 Length | 40.0 cm |
|------------------|---------|

---

|                  |          |
|------------------|----------|
| Package 2 Weight | 4.451 kg |
|------------------|----------|

## Contractual warranty

---

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Total lifecycle Carbon footprint 21

Environmental Disclosure [Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard No

Packaging without single use plastic No

[EU RoHS Directive](#) Compliant with Exemptions

SCIP Number B0741fa4-2bd9-44d3-a946-cc026d2e56d0

REACH Regulation [REACH Declaration](#)

Halogen-free status Product contains halogen above thresholds

Silicone-free No

## Use Again

### Repack and remanufacture

Recyclability potential, in % 65

End of life manual availability [End of Life Information](#)

Take-back No

WEEE Label  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins