

Product datasheet

Specifications



spreaders 45 mm to 70 mm pitch, ComPact NSX 400/630, 3 poles, set of 3 parts

Local distributor code:
399371990

LV432492

EAN Code: 3606480019678

Main

Product or component type	Spreader
Accessory / separate part category	Connection accessory
Range compatibility	ComPacT ComPacT NSX400 ComPacT ComPacT NSX630 ComPacT ComPacT NSX DC ComPact ComPact NSX400 ComPact ComPact NSX630 ComPact Compact NSX400 DC ComPact Compact NSX630 DC EasyPact EasyPact CVS400 EasyPact EasyPact CVS630 ComPact ComPacT INS ComPact Compact INV
Poles description	3P
Quantity per set	3
Mounting position	Straight

Complementary

[In] rated current	630 A
Connection pitch	70 mm

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.000 cm
Package 1 Width	20.000 cm
Package 1 Length	22.000 cm
Package 1 Weight	1.043 kg
Unit Type of Package 2	S03
Number of Units in Package 2	12
Package 2 Height	30.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	12.926 kg
Unit Type of Package 3	P12
Number of Units in Package 3	96

Package 3 Height	42.000 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	114.205 kg

Logistical informations

Country of origin FR

Contractual warranty

Warranty 18 months



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Total lifecycle Carbon footprint 6

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard Yes

Packaging without single use plastic No

[EU RoHS Directive](#) Compliant

REACH Regulation [REACH Declaration](#)

Halogen-free status Product contains halogen above thresholds

Use Again

Repack and remanufacture

Recyclability potential, in % 83

End of life manual availability No need of specific recycling operations

Take-back No