

Product datasheet

Specifications



residual current protection relay,
Vigirex RHU, 30 mA to 30 A,
220/240 VAC 50/60Hz,
communicating, front panel
mounting

LV481003

EAN Code: 3606485434728

Main

Range	VigiPacT
Device short name	RHU
Product or component type	Residual current protection relay
Relay application	Monitoring relay Protection relay
Mounting support	Front panel
Earth-leakage protection class	Type A
Type of setting	Modbus address Keypad
Residual earth-leakage sensitivity adjustment type	Adjustable
Earth-leakage sensitivity	0.03...1 A, adjustable in step of 0.001 A 1...30 A, adjustable in step of 0.1 A
Earth-leakage time delay	Instantaneous for 0.03 A Adjustable 0...4.5 s for 0.03...30 A adjustable in step of 10 ms
Threshold setting	0.015...1 A adjustable in step of 0.001 A pre-alarm 1...30 A adjustable in step of 0.1 A pre-alarm 0.03...1 A adjustable in step of 0.001 A alarm 1...30 A adjustable in step of 0.1 A alarm
Current sensors compatibility	VigiPacT TOA earth leakage current sensor VigiPacT A earth leakage current sensor VigiPacT L earth leakage current sensor
[I _{th}] conventional enclosed thermal current	8 A
Minimum load	10 mA at 12 V
[U _s] rated supply voltage	220...240 V AC 50/60 Hz 70...110 %
Power consumption in VA	8 VA
Monitored distribution system	1000 V - AC at 50/60 Hz (maximum) 1000 V - AC at 400 Hz (maximum)
Earthing system	TT TN-S IT
[U _{imp}] rated impulse withstand voltage	8 kV
Reset	Remote reset

Complementary

Test function	Remote test Remote test (via communication) Local
Signal contacts composition	1 C/O alarm fail-safe 1 NO pre-alarm fail-safe
Type of measurement	Earth fault current internal measurement, range: 20...200 %, accuracy: +/- 20 %
Refresh time	0.5 s
Communication service	Modbus slave
Tamperproof of settings	Protected by access code
Connections - terminals	Alarm circuit: terminal block cable(s) 0.2...2.5 mm ² flexible AWG 22...AWG 12 Alarm circuit: terminal block cable(s) 0.2...2.5 mm ² rigid AWG 22...AWG 12 Relay test and fault reset: terminal block cable(s) 0.2...2.5 mm ² flexible AWG 22...AWG 12 Relay test and fault reset: terminal block cable(s) 0.2...2.5 mm ² rigid AWG 22...AWG 12 Sensor: terminal block cable(s) 0.2...2.5 mm ² flexible AWG 22...AWG 12 Sensor: terminal block cable(s) 0.2...2.5 mm ² rigid AWG 22...AWG 12 Voltage presence: terminal block cable(s) 0.2...2.5 mm ² flexible AWG 22...AWG 12 Voltage presence: terminal block cable(s) 0.2...2.5 mm ² rigid AWG 22...AWG 12 Power supply: terminal block cable(s) 0.2...2.5 mm ² flexible AWG 22...AWG 12 Power supply: terminal block cable(s) 0.2...2.5 mm ² rigid AWG 22...AWG 12 Pre alarm: terminal block cable(s) 0.2...2.5 mm ² flexible AWG 22...AWG 12 Pre alarm: terminal block cable(s) 0.2...2.5 mm ² rigid AWG 22...AWG 12
Wire stripping length	Alarm circuit: 6 mm Relay test and fault reset: 6 mm Sensor: 6 mm Voltage presence: 6 mm Power supply: 6 mm Pre alarm: 6 mm
Tightening torque	Alarm circuit: 0.5 N.m Relay test and fault reset: 0.5 N.m Sensor: 0.5 N.m Voltage presence: 0.5 N.m Power supply: 0.5 N.m Pre alarm: 0.5 N.m
Standards	EN/IEC 60947-2 Annex M EN/IEC 60755
Width	72 mm
Height	72 mm
Depth	117 mm
Cut-out dimensions	68 x 68 mm
Net weight	0.3 kg
IP degree of protection	IP40 front face: conforming to IEC 60529 IP30 other parts: conforming to IEC 60529 IP20 connection: conforming to IEC 60529
IK degree of protection	IK07 conforming to EN 50102
Mechanical robustness	Vibrations 13.2...100 Hz: 0.7 g Vibrations 2...13.2 Hz: +/- 1 mm

Environment

Environmental characteristic	Exposure to damp heat not in service conforming to IEC 60068-2-30 Exposure to damp heat in service conforming to IEC 60068-2-56 Salt mist conforming to IEC 60068-2-52
Overvoltage category	IV
Electrical shock protection class	Class II

Electromagnetic compatibility	Conducted and radiated emissions: , B, conforming to CISPR 11 Conducted radio-frequency immunity test: , 3, conforming to IEC 61000-4-6 Electrostatic discharge immunity test: , 4, conforming to IEC 61000-4-2 High-energy conducted susceptibility: , 4, conforming to IEC 61000-4-5 Low-energy conducted susceptibility: , 4, conforming to IEC 61000-4-4 Radiated susceptibility: , 3, conforming to IEC 61000-4-3
Relative humidity	95 % at 55 °C
Pollution degree	3 conforming to IEC 60664-1
Ambient air temperature for operation	-25...55 °C
Ambient air temperature for storage	-40...85 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.5 cm
Package 1 Width	11.0 cm
Package 1 Length	15.5 cm
Package 1 Weight	430.0 g
Unit Type of Package 2	S04
Number of Units in Package 2	24
Package 2 Height	30.0 cm
Package 2 Width	40.0 cm
Package 2 Length	60.0 cm
Package 2 Weight	11.086 kg

Logistical informations

Country of origin	FR
--------------------------	----

Contractual warranty

Warranty	18 months
-----------------	-----------



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Total lifecycle Carbon footprint **161**

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard **Yes**

Packaging without single use plastic **No**

[EU RoHS Directive](#) **Compliant with Exemptions**

SCIP Number **6b2913b0-ca83-4683-bb4c-744a8bb90c08**

REACH Regulation [REACH Declaration](#)

Halogen-free status **Halogen free plastic parts product**

Use Again

Repack and remanufacture

Recyclability potential, in % **0**

End of life manual availability [End of Life Information](#)

Take-back **No**

WEEE Label  **The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins**

Technical Illustration

Assembly's dimensions

