

Product datasheet

Specifications



Auxiliary contact, Multi9 M9A, OF, 1 C/O, 100mA to 6A, 24VAC to 415VAC, 24VDC to 130VDC, bottom connection

M9A26904

EAN Code: 3606486351802

Main

range of product	Multi9
Product or component type	OC contact
Device short name	OF
Signal contacts composition	1 C/O
[In] rated current	0.1...6 A at 24...240 V, AC 50/60 Hz 0.1...6 A at 24...250 V, AC 50/60 Hz 0.1...6 A at 24 V, DC 0.1...2 A at 48 V, DC 0.1...1.5 A at 60 V, DC 0.1...1 A at 110 V, DC 0.1...1 A at 130 V, DC 0.1...3 A at 277 V, AC 50/60 Hz 0.1...3 A at 415 V, AC 50/60 Hz
9 mm pitches	1
Standards	EN/IEC 60947-5-1 GB/T 14048.5 EN 62019-2 UL 1077 UL 489 C22.2 No. 5 C22.2 No. 235
Product certifications	CE UKCA UL
Quality labels	EAC CCC

Complementary

Range compatibility	Multi9 C60BP Multi9 C60SP Multi9 C60 Multi9 N40
[Ui] rated insulation voltage	500 V
[Uimp] rated impulse withstand voltage	4 kV
Mounting mode	Clip-on
Mounting location	Left side of circuit-breaker
Mounting support	DIN rail
Comb busbar and distribution block compatibility	Top: YES
Height	85 mm
Width	9 mm

Depth	68 mm
Net weight	30 g
Colour	Grey
Connections - terminals	Screw clamp terminal (bottom) 1 cable(s) 2.5 mm ² - rigid Screw clamp terminal (bottom) 2 cable(s) 1.5 mm ² - rigid
Wire stripping length	9 mm
Tightening torque	1 N.m bottom

Environment

IP degree of protection	IP20
Pollution degree	3
Tropicalisation	2
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...85 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.800 cm
Package 1 Width	7.500 cm
Package 1 Length	9.400 cm
Package 1 Weight	36.000 g
Unit Type of Package 2	BB1
Number of Units in Package 2	12
Package 2 Height	8.500 cm
Package 2 Width	10.000 cm
Package 2 Length	23.500 cm
Package 2 Weight	484.000 g
Unit Type of Package 3	S03
Number of Units in Package 3	108
Package 3 Height	30.000 cm
Package 3 Width	30.000 cm
Package 3 Length	40.000 cm
Package 3 Weight	4.980 kg

Contractual warranty

Warranty	18 months
----------	-----------



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Total lifecycle Carbon footprint 1

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard No

Packaging without single use plastic No

[EU RoHS Directive](#) Compliant

SCIP Number 28bfb466-f950-4025-8655-16cfe4e6c6f3

REACH Regulation [REACH Declaration](#)

Use Again

Repack and remanufacture

Recyclability potential, in % 40

Take-back No

WEEE Label  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins