

Product datasheet

Specifications



Multi9 - OC contact - 1 OF - 240/415 V AC - 24/130 V DC

M9A26924

⚠ Discontinued on: 15 Feb 2024

⚠ End-of-service on: 15 Feb 2025

⚠ Discontinued

EAN Code: 3606480639043

Main

range of product	Multi9
Product or component type	OC contact
Device short name	OF
Signal contacts composition	1 C/O
[In] rated current	3 A at 415 V, AC 50/60 Hz 6 A at <= 240 V, AC 50/60 Hz
[Uc] control circuit voltage	240...415 V AC 50/60 Hz 24...130 V DC
9 mm pitches	1
Standards	EN/IEC 60947-5-1 EN 62019-2
Product certifications	CSA UR UL CCC PCT

Complementary

Range compatibility	Multi9 C60BPR Multi9 C60H-DC Multi9 C60SP Multi9 C60BP
[Ui] rated insulation voltage	500 V
[Uimp] rated impulse withstand voltage	4 kV
Mounting mode	Fixed
Mounting support	DIN rail
Comb busbar and distribution block compatibility	Top: YES
Height	85 mm
Width	9 mm
Depth	73.5 mm
Net weight	0.03 kg
Connections - terminals	Clamp terminal (bottom) 1 cable(s) 2.5 mm ² (AWG 14) - rigid Clamp terminal (bottom) 2 cable(s) 1.5 mm ² (AWG 16) - rigid
Wire stripping length	9 mm for bottom connection
Tightening torque	1 N.m bottom

Environment

Ambient air temperature for operation	-25...50 °C
Ambient air temperature for storage	-40...85 °C

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
------------------------------	---

Package 1 Height	2.1 cm
------------------	--------

Package 1 Width	8 cm
-----------------	------

Package 1 Length	9.5 cm
------------------	--------

Package 1 Weight	37 g
------------------	------

Unit Type of Package 2	BB1
------------------------	-----

Number of Units in Package 2	12
------------------------------	----

Package 2 Height	8.5 cm
------------------	--------

Package 2 Width	10 cm
-----------------	-------

Package 2 Length	26.5 cm
------------------	---------

Package 2 Weight	512 g
------------------	-------

Unit Type of Package 3	S03
------------------------	-----

Number of Units in Package 3	108
------------------------------	-----

Package 3 Height	30 cm
------------------	-------

Package 3 Width	30 cm
-----------------	-------

Package 3 Length	40 cm
------------------	-------

Package 3 Weight	5.009 kg
------------------	----------

Contractual warranty

Warranty	18 months
----------	-----------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

Use Better

Materials and Substances

[EU RoHS Directive](#)

Compliant

SCIP Number

28bfb466-f950-4025-8655-16cfe4e6c6f3

REACH Regulation

[REACH Declaration](#)

Use Again

Repack and remanufacture

End of life manual availability

[End of Life Information](#)

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins