

Product datasheet

Specifications



ClimaSys forced vent. IP54, 85m3/h, 230V, with outlet grille and filter G2

Local distributor code:

388827691

NSYCVF85M230PF

EAN Code: 3606480151200

Main

Range	ClimaSys
Product name	ClimaSys CV
Product or component type	Fan
Type of filter	Standard
Flow rate	Free flow rate with standard filter: 85 m3/h at 50 Hz Free flow rate with standard filter: 98 m3/h at 60 Hz
[Us] rated supply voltage	175...253 V
Input voltage	230 V 50/60 Hz
Certification	CSA

Complementary

Absorbed power	15 W 60 Hz 17 W 50 Hz
[In] rated current	0.121 A 50 Hz 0.097 A 60 Hz
Noise level < at	46...49 dB
Bearing type	Ball
Height	External: 170 mm
Width	External: 150 mm
Depth	External : 62 mm
Cut-out dimensions	125 x 125 mm
Net weight	0.78 kg
Material	Outlet grille: injected thermoplastic (ASA PC)
Colour	Outlet grille: grey (RAL 7035)
Ambient air temperature for operation	-20...60 °C
Ambient air temperature for storage	-40...70 °C
Maximum pressure	50 Pa flow rate 0 m³/h
Connections - terminals	Faston connector
IP degree of protection	IP54
Device composition	1 axial motor 2 protective grille: on the front and rear surfaces 1 filter: front of axial motor 1 outlet grille: front 1 cut-out template 1 power cord

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Condition of use	<p>Flow rates depends on the work point, see ProClima software</p> <p>Surrounding environment must be relatively clean</p> <p>Filter must be cleaned and replaced regularly</p> <p>Overfrequent filter replacement should be avoided</p> <p>Outside temperature must be 5 °C lower than inside temperature</p>
-------------------------	--

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.000 cm
Package 1 Width	15.500 cm
Package 1 Length	18.000 cm
Package 1 Weight	930.000 g
Unit Type of Package 2	CAR
Number of Units in Package 2	10
Package 2 Height	21.000 cm
Package 2 Width	33.000 cm
Package 2 Length	43.000 cm
Package 2 Weight	9.526 kg
Unit Type of Package 3	P12
Number of Units in Package 3	240
Package 3 Height	95.000 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	241.000 kg

Contractual warranty

Warranty	18 months
-----------------	-----------



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Total lifecycle Carbon footprint **9**

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard **No**

Packaging without single use plastic **No**

[EU RoHS Directive](#) **Compliant with Exemptions**

SCIP Number **61d9d3f3-5a49-48f8-8056-1a5ad0ad4c76**

REACH Regulation [REACH Declaration](#)

Use Again

Repack and remanufacture

Recyclability potential, in % **64**

Take-back **No**

WEEE Label  **The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins**