

# Product datasheet

Specifications



## Control window IP 55 with aluminum frame and 3 mm acrylic window 500 x 500 mm

NSYCW55

EAN Code: 3606480724534

### Main

Range	PanelSeT
Accessory / separate part category	Installation accessory
Product or component type	Window
For enclosure nominal dimensions	-
Range compatibility	PanelSeT S3D PanelSeT CRN
Mounting location	Installation on door or panel
Device composition	2 hinge 1 lock 1 fixings and drilling template 1 frame with window
Material	Transparent acrylic aluminium
Lock type	Closure by lock
Number of locks	1
Key number	2233X

### Complementary

Height	500 mm
Width	500 mm
Depth	77 mm
Type of installation	Indoor installation

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	56.500 cm
Package 1 Width	53.000 cm
Package 1 Length	12.000 cm
Package 1 Weight	4.410 kg
Unit Type of Package 2	PAM
Number of Units in Package 2	40
Package 2 Height	155.000 cm
Package 2 Width	100.000 cm

---

Package 2 Length	120.000 cm
------------------	------------

---

Package 2 Weight	189.000 kg
------------------	------------

## Logistical informations

---

Country of origin	DE
-------------------	----

## Contractual warranty

---

Warranty	18 months
----------	-----------

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard

No

Packaging without single use plastic

No

[EU RoHS Directive](#)

Pro-active compliance (Product out of EU RoHS legal scope)

SCIP Number

86c971db-94b7-45f1-bdf1-8c503ea9309d

REACH Regulation

[REACH Declaration](#)

## Use Again

### Repack and remanufacture

End of life manual availability

No need of specific recycling operations

Take-back

No