

Product datasheet

Specifications



"Wall mounted steel enclosure,
PanelSeT S3D, double plain door,
with mounting plate,
1400x1000x300mm, IP55, IK10"

Local distributor code:

392867391

NSYS3D141030DP

EAN Code: 3606480159817

Main

| | |
|-----------------------------|---|
| Range | PanelSeT |
| Product name | PanelSeT S3D |
| Application | Multi-purpose |
| Category | Compact enclosure |
| Enclosure nominal height | 1400 mm |
| Enclosure nominal width | 1000 mm |
| Enclosure nominal depth | 300 mm |
| Door type | Plain |
| Mounting plate description | Plain |
| Type of gland plate | Standard |
| Installation accessory type | Wall-mounting |
| Device composition | 1 body 2 cable gland plate 2 door with lock 1 mounting plate |

Complementary

| | |
|-----------------------------|---|
| body type | Gutter-shaped front rail double sheet thickness Single piece body |
| Number of doors | Front face: 2 door(s) |
| Door opening side | Reversible (120 °) |
| Lock type | 3 points lock, 3 mm double-bar |
| Accessibility for operation | Front |
| Removable parts | Door by hinges Cable gland plate by screws Mounting plate by fixing element |
| Material | Enclosure: steel Mounting plate: galvanised steel |
| Surface finish | Enclosure: epoxy-polyester powder |
| Colour | Enclosure: grey (RAL 7035) |
| Standards | IEC 62208 UL CUL |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|-------------------------------|------------------------------|
| Product certifications | DNV GL cUL UL BV |
|-------------------------------|------------------------------|

| | |
|-------------------|--------|
| Net weight | 107 kg |
|-------------------|--------|

Environment

| | |
|--------------------------------|------------------------------|
| IK degree of protection | IK10 conforming to IEC 62262 |
|--------------------------------|------------------------------|

| | |
|--------------------------------|------------------------------|
| IP degree of protection | IP55 conforming to IEC 60529 |
|--------------------------------|------------------------------|

Packing Units

| | |
|-------------------------------|-----|
| Unit Type of Package 1 | PCE |
|-------------------------------|-----|

| | |
|-------------------------------------|---|
| Number of Units in Package 1 | 1 |
|-------------------------------------|---|

| | |
|-------------------------|------------|
| Package 1 Height | 153.000 cm |
|-------------------------|------------|

| | |
|------------------------|------------|
| Package 1 Width | 103.000 cm |
|------------------------|------------|

| | |
|-------------------------|-----------|
| Package 1 Length | 36.000 cm |
|-------------------------|-----------|

| | |
|-------------------------|------------|
| Package 1 Weight | 108.000 kg |
|-------------------------|------------|

Logistical informations

| | |
|--------------------------|----|
| Country of origin | FR |
|--------------------------|----|

Contractual warranty

| | |
|-----------------|--------------|
| Coverage | Core product |
|-----------------|--------------|

| | |
|-----------------|-----------|
| Warranty | 18 months |
|-----------------|-----------|

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Total lifecycle Carbon footprint 1017

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard No

Packaging without single use plastic No

[EU RoHS Directive](#) Pro-active compliance (Product out of EU RoHS legal scope)

SCIP Number E893f0a0-d2cc-4011-9425-3873dde70142

REACH Regulation [REACH Declaration](#)

Use Again

Repack and remanufacture

Recyclability potential, in % 98

End of life manual availability No need of specific recycling operations

Take-back No

Offer Marketing Illustration

Product benefits / Features



Sturdy components' protection

Earthing studs included

Large choice of dimensions & accessories

Quality & aesthetics

Easy to equip
Easy to maintain

Reusable eco-friendly packaging