

# Product datasheet

Specifications



## " PanelSeT S3D Wall mounted steel, plain door, with mounting plate, 400x400x200mm, IP66, IK10"

Local distributor code:

392866114

NSYS3D4420P

**EAN Code: 3606480159565**

### Main

Range	PanelSeT
Product name	PanelSeT S3D
Application	Multi-purpose
Category	Compact enclosure
Enclosure nominal height	400 mm
Enclosure nominal width	400 mm
Enclosure nominal depth	200 mm
Door type	Plain
Mounting plate description	Plain
Type of gland plate	Standard
Installation accessory type	Wall-mounting
Device composition	1 body 1 mounting plate 1 door with lock 1 cable gland plate

### Complementary

body type	Gutter-shaped front rail double sheet thickness Single piece body
Number of doors	Front face: 1 door(s)
Door opening side	Reversible (120 °)
Lock type	3 mm double-bar lock
Accessibility for operation	Front
Removable parts	Door by hinges Cable gland plate by screws Mounting plate by fixing element
Material	Enclosure: steel Mounting plate: galvanised steel
Surface finish	Enclosure: epoxy-polyester powder
Colour	Enclosure: grey (RAL 7035)
Standards	IEC 62208 UL CUL
Product certifications	UL cUL DNV GL BV

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

---

Net weight	8 kg
------------	------

## Environment

---

NEMA degree of protection	NEMA 4X/13
---------------------------	------------

---

IK degree of protection	IK10 conforming to IEC 62262
-------------------------	------------------------------

---

IP degree of protection	IP66 conforming to IEC 60529
-------------------------	------------------------------

## Packing Units

---

Unit Type of Package 1	PCE
------------------------	-----

---

Number of Units in Package 1	1
------------------------------	---

---

Package 1 Height	42.000 cm
------------------	-----------

---

Package 1 Width	42.000 cm
-----------------	-----------

---

Package 1 Length	42.000 cm
------------------	-----------

---

Package 1 Weight	8.670 kg
------------------	----------

---

Unit Type of Package 2	PAM
------------------------	-----

---

Number of Units in Package 2	40
------------------------------	----

---

Package 2 Height	182.000 cm
------------------	------------

---

Package 2 Width	100.000 cm
-----------------	------------

---

Package 2 Length	120.000 cm
------------------	------------

---

Package 2 Weight	360.500 kg
------------------	------------

## Logistical informations

---

Country of origin	FR
-------------------	----

## Contractual warranty

---

Coverage	Core product
----------	--------------

---

Warranty	18 months
----------	-----------



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Total lifecycle Carbon footprint 92

Environmental Disclosure [Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard No

Packaging without single use plastic No

[EU RoHS Directive](#) Pro-active compliance (Product out of EU RoHS legal scope)

SCIP Number E893f0a0-d2cc-4011-9425-3873dde70142

REACH Regulation [REACH Declaration](#)

## Use Again

### Repack and remanufacture

Recyclability potential, in % 98


End of life manual availability No need of specific recycling operations

Take-back No

Technical Illustration

Dimensions

---



Offer Marketing Illustration

Product benefits / Features

---



Sturdy components' protection

Earthing studs included

Large choice of dimensions & accessories

Quality & aesthetics

Easy to equip  
Easy to maintain

Reusable eco-friendly packaging