

# Product datasheet

Specifications



## "PanelSet S3X stainless 304L, Scotch Brite® finish, H600xW600xD250 mm."

Local distributor code:

381201544

NSYS3X6625

**EAN Code: 3606480155246**

## Main

Range	Spacial
Product name	Spacial S3X
enclosure type	Multi-purpose
category	Compact enclosure
nominal height	600 mm
nominal width	600 mm
nominal depth	250 mm
product installation	Wall-mounting
Device composition	1 body 1 door 2 lock: door 2 perforated vertical profile drilled: door

## Complementary

Body type	Single piece body, cross-shaped structure Gutter shaped front rail
Door type	Plain
Number of doors	Front face: 1 door(s)
Door opening side	Reversible (120 °)
Lock type	2 points lock, 3 mm double-bar
Mounting plate description	Without mounting plate
Type of gland plate	Without gland plate
Accessibility for operation	Front
Removable parts	Door by hinges
Material	Body and door: stainless steel 304L Lock: zamak Hinge: stainless steel
Surface finish	Body and door: Scotch-Brite® brushed Lock: chromium plated
Net weight	13.902 kg

## Environment

Standards	IEC 62208 UL CUL
-----------	------------------------

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

<b>Product certifications</b>	UL 508 type A CAN/CSA 22
<b>IP degree of protection</b>	IP66 conforming to IEC 60529
<b>IK degree of protection</b>	IK10 conforming to IEC 62262
<b>Environmental characteristic</b>	Corrosive Specific hygiene

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	26.500 cm
<b>Package 1 Width</b>	61.000 cm
<b>Package 1 Length</b>	61.500 cm
<b>Package 1 Weight</b>	13.902 kg
<b>Unit Type of Package 2</b>	PAL
<b>Number of Units in Package 2</b>	18
<b>Package 2 Height</b>	198.000 cm
<b>Package 2 Width</b>	100.000 cm
<b>Package 2 Length</b>	122.000 cm
<b>Package 2 Weight</b>	271.000 kg

## Logistical informations

<b>Country of origin</b>	BG
--------------------------	----

## Contractual warranty

<b>Warranty</b>	18 months
-----------------	-----------

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Total lifecycle Carbon footprint 207

Environmental Disclosure [Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard No

Packaging without single use plastic No

[EU RoHS Directive](#) Pro-active compliance (Product out of EU RoHS legal scope)

SCIP Number E893f0a0-d2cc-4011-9425-3873dde70142

REACH Regulation [REACH Declaration](#)

## Use Again

### Repack and remanufacture


End of life manual availability No need of specific recycling operations

Take-back No

Technical Illustration

Dimensions

---



Offer Marketing Illustration

Product benefits / Features

---

High resistance to corrosion

Earthing studs included

Large choice of dimensions & accessories

Built to last

Easy to equip  
Easy to maintain

Easy & quick assembly