

Product datasheet

Specifications



ConneXium Industrial Firewall - 2 ports for copper

TCSEFEC23F3F21

EAN Code: 3606480757983

Main

Range of product	Modicon Networking
Product or component type	Ethernet TCP/IP firewall
Communication port protocol	Ethernet TCP/IP SSH HTTP HTTPS SNMP SFTP SCP LLDP RS232
Port Ethernet	10/100BASE-TX - 2 port(s) copper cable
Cybersecurity	Syslog protocol support IPSec
User interface	Built-in firewall
Encryption protocol	MAC addresses filtering

Complementary

Integrated connection type	Shielded RJ45 copper cable
Transmission support medium	Twisted shielded pairs cable CAT 5E for copper cable
Maximum cable distance between devices	100 m copper cable
Ethernet service	Multicast filtering Syslog
Communication service	Port monitoring
Diagnostics run time	Signal contact Self test MAC notification
Redundancy	Redundant network coupling Router redundancy
[Us] rated supply voltage	12...48 V
Supply voltage limits	9.6...60 V DC SELV 18...30 V AC SELV
Power consumption in W	6.9 W
Electrical connection	Removable connector 6 ways power supply
Mounting support	35 mm symmetrical DIN rail
Marking	CE UL RCM

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Function available	System information Report IP Firewall list Configuration check Reachability test (ping) Alarms (Traps)
Local signalling	2 LEDs (green) for P1 P2 power supplies 1 LED (red) for fault 1 dual colour LED (green/yellow) for device status 1 dual colour LED (green/yellow) for memory key status 1 dual colour LED (green/yellow) for internal port status 1 dual colour LED (green/yellow) for serial port status
Alarm output	1 voltfree contact 1 A
Alarm function	Power supply fault Data link status Switch fault Temperature threshold External memory removed
Ethernet cabling system	TF switches
Width	60 mm
Height	145 mm
Depth	125 mm
Net weight	0.61 kg

Environment

Ambient air temperature for operation	0...60 °C
Relative humidity	10...95 % non-condensing
IP degree of protection	IP20
Directives	2014/35/EU - low voltage directive 2014/30/EU - electromagnetic compatibility
Standards	UL 508 EN/IEC 61131 EN/IEC 60950
Product certifications	CE UL RCM UKCA DNV

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	21.000 cm
Package 1 Width	22.000 cm
Package 1 Length	22.500 cm
Package 1 Weight	1.031 kg
Unit Type of Package 2	S04
Number of Units in Package 2	2
Package 2 Height	30.000 cm
Package 2 Width	40.000 cm
Package 2 Length	60.000 cm

Package 2 Weight 2.700 kg

Logistical informations

Country of origin DE

Contractual warranty

Warranty 18 months


Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.


[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

 Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
REACH Regulation	REACH Declaration

Use Again

 Repack and remanufacture	
Take-back	No

Dimensions Drawings

Dimensions

