

# Product datasheet

Specifications



## SIL interface module, TeSys island

Local distributor code:

425225729

TPRSM001

**EAN Code: 3606489832872**

### Main

<b>Range</b>	TeSys
<b>Product name</b>	TeSys island
<b>Device short name</b>	TPRSM
<b>Product or component type</b>	SIL interface module
<b>Device presentation</b>	Implementation of a safe stop function for SIL motor starters TPRSS Safe stop operable for safety-related system conforming to ISO 13849-1 Operational only when connected to a bus coupler TPRBC
<b>Function of module</b>	Safe stop with 1NC or 2NC contacts monitoring
<b>Product compatibility</b>	TPRBC bus coupler TPRSS SIL motor starter
<b>[Ue] rated operational voltage</b>	Input/output circuit: 24 V DC
<b>[Ui] rated insulation voltage</b>	Input/output circuit: 50 V
<b>[Uimp] rated impulse withstand voltage</b>	2 kV for input/output circuit conforming to IEC 60947-1
<b>Overvoltage category</b>	III
<b>Input type</b>	Isolated switching input for safe stop
<b>Input protection type</b>	Internal, electronic
<b>Input voltage</b>	15...28.8 V DC state 1 0...5 V DC state 0
<b>Output type</b>	Relay instantaneous opening, 1 NO circuit(s), potential free
<b>Output thermal current</b>	8 A for relay output
<b>Protection type</b>	External fuse, 8 A gG fuse for relay output
<b>Local signalling</b>	1 LED (green/red) for DS (device status) 1 LED (green/red) for SS (safe stop status)

### Complementary

<b>[Us] rated supply voltage</b>	24 V DC supplied by the bus coupler
<b>Current consumption</b>	10 mA
<b>Power dissipation in W</b>	0.7 W maximum
<b>Safety function</b>	Safe stop: category 0 conforming to IEC 60204-1 Safe stop: category 1 conforming to IEC 60204-1
<b>Safety integrity level</b>	SIL 2 conforming to IEC 61508 in single channel system architecture SILCL 2 conforming to IEC 62061 in single channel system architecture PL = d category 2 conforming to ISO 13849-1 in single channel system architecture
<b>Standards</b>	UL 60947-5-1 IEC 60947-5-1

<b>Product certifications</b>	EAC (pending) UL CSA
<b>Mounting mode</b>	Horizontal and vertical (35 mm symmetrical rail)
<b>Connections - terminals</b>	Control circuit: removable spring terminal block 5 cable(s) 0.2...2.5 mm <sup>2</sup> (AWG 24...AWG 14) rigid Control circuit: removable spring terminal block 5 cable(s) 0.2...2.5 mm <sup>2</sup> (AWG 24...AWG 14) flexible without cable end Control circuit: removable spring terminal block 5 cable(s) 0.25...2.5 mm <sup>2</sup> (AWG 22...AWG 14) flexible with cable end
<b>Width</b>	25 mm
<b>Height</b>	118 mm
<b>Depth</b>	114 mm
<b>Net weight</b>	0.159 kg

## Environment

<b>Ambient air temperature for storage</b>	-25...70 °C
<b>Ambient air temperature for operation</b>	-10...60 °C
<b>Relative humidity</b>	5...95 %
<b>Operating altitude</b>	0...2000 m without derating
<b>IP degree of protection</b>	IP20
<b>Pollution degree</b>	2
<b>Protective treatment</b>	TC
<b>Fire resistance</b>	960 °C conforming to UL 94
<b>Shock resistance</b>	15 gn (duration = 11 ms) conforming to IEC 60068-2-27
<b>Vibration resistance</b>	1.5 mm peak to peak (f= 3...13 Hz) conforming to IEC 60068-2-6 1 gn (f= 13...200 Hz) conforming to IEC 60068-2-6
<b>Electromagnetic compatibility</b>	Electrostatic discharge, level 3, 8 kV air, 6 kV contact, conforming to EN/IEC 61000-4-2 Radiated RF fields, level 3, 10 V/m, conforming to EN/IEC 61000-4-3 Fast transients immunity test, level 3, 2 kV, conforming to EN/IEC 61000-4-4 Surge immunity test (common mode), level 3, 2 kV, conforming to EN/IEC 61000-4-5

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	6.500 cm
<b>Package 1 Width</b>	13.500 cm
<b>Package 1 Length</b>	15.500 cm
<b>Package 1 Weight</b>	270.000 g
<b>Unit Type of Package 2</b>	S03
<b>Number of Units in Package 2</b>	16
<b>Package 2 Height</b>	30.000 cm
<b>Package 2 Width</b>	30.000 cm
<b>Package 2 Length</b>	40.000 cm
<b>Package 2 Weight</b>	5.019 kg

## Logistical informations

---

Country of origin ID

## Contractual warranty

---

Warranty 18 months

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard

Yes

Packaging without single use plastic

No

[EU RoHS Directive](#)

Compliant with Exemptions

SCIP Number

B164c55a-185e-47e2-96d5-e03c25b77067

Halogen-free status

Halogen free plastic parts product

## Use Again

### Repack and remanufacture


End of life manual availability

[End of Life Information](#)

Take-back

No

WEEE Label

 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Technical Illustration

Assembly's dimensions

---

