

# Product datasheet

Specifications



Delta 3 robot, P0, 3-4 axis, 10 kg permissible load, 0-400 mm working envelop

VRKP0S0RNC00000

EAN Code: 3606481732811

## Main

Range of product	Lexium P, T
Device short name	P0
Product or component type	Delta 3 robot
Design	Compact

## Complementary

Number of axis	3
Operating position	Rotational 360°
Operating travel	0...400 mm horizontal 0...144 mm vertical
Repeat accuracy	0.05 mm
Permanent permissible load	10 kg
Maximum actuation speed	6 m/s
Maximum acceleration	125 m/s <sup>2</sup> at 1 kg 120 m/s <sup>2</sup> at 1.5 kg
Net weight	27.6 kg
Range compatibility	Lexium SH3 motor

## Environment

Environmental characteristic	Normal environment
------------------------------	--------------------

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	92.000 cm
Package 1 Width	120.500 cm
Package 1 Length	120.500 cm
Package 1 Weight	47.000 kg

## Logistical informations

Country of origin	DE
-------------------	----

## Contractual warranty

Warranty	18 months
----------	-----------

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Total lifecycle Carbon footprint 15761

Environmental Disclosure [Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard Yes

Packaging without single use plastic No

[EU RoHS Directive](#) Pro-active compliance (Product out of EU RoHS legal scope)

REACH Regulation [REACH Declaration](#)

## Use Again

### Repack and remanufacture

End of life manual availability [End of Life Information](#)

Take-back No

Image of product / Alternate images

Alternative

---





