

Product datasheet

Specifications



Base unit kit, Harmony XVM, Ø 45 mm, white, IP40, screw terminals

XVMC213T

⚠ Discontinued on: 7 Aug 2023

EAN Code: 3389119004336

⚠ Discontinued

Main

Range of product	Harmony XVM
Product or component type	Base unit kit
Kit composition	Bracket 250 mm support tube Base unit Cover
Component name	XVM
Indicator bank base type	Base without buzzer

Complementary

Mounting diameter	45 mm
Housing colour	White
Connections - terminals	Screw terminals, 1 x 0.325...1 x 1.5 mm ²
Marking	CE
Net weight	0.298 kg

Environment

Standards	IEC 60947-1 IEC 60947-5-1
Product certifications	CCC
Ambient air temperature for storage	-25...70 °C
Ambient air temperature for operation	-10...50 °C
Electrical shock protection class	Class I aluminium tube mounting conforming to IEC 60947-1 Class I aluminium tube mounting conforming to IEC 60947-5-1 Class I aluminium tube mounting conforming to IEC 61140
IP degree of protection	IP40 any position except vertical position conforming to IEC 60529 IP42 vertical position conforming to IEC 60529
Protective treatment	TC

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5 cm
Package 1 Width	5.5 cm

Package 1 Length	32 cm
Package 1 Weight	292 g
Unit Type of Package 2	S02
Number of Units in Package 2	15
Package 2 Height	15 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	4.835 kg

Contractual warranty

Warranty	18 months
----------	-----------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard

Yes

Packaging without single use plastic

Yes

[EU RoHS Directive](#)

Pro-active compliance (Product out of EU RoHS legal scope)

SCIP Number

6797f094-b2bf-48a4-981a-58794615fad0

Use Again

Repack and remanufacture


End of life manual availability

No need of specific recycling operations

Connections and Schema

Customer Assembled Tower Light

Wiring Diagram



Indicator bank with buzzer (4 illuminated units max.):

- 4: 4th illuminated unit
- 3: 3rd illuminated unit
- 2: 2nd illuminated unit
- 1: 1st illuminated unit

N: Common

B: Buzzer

Indicator bank without buzzer:

- 5: 5th illuminated unit
- 4: 4th illuminated unit
- 3: 3rd illuminated unit
- 2: 2nd illuminated unit
- 1: 1st illuminated unit

N: Common

Maximum capacity for wiring through support tube:

- 6 wires x 1 mm²/16 AWG,
- 5 wires x 1.5 mm²/14 AWG