

Product datasheet

Specifications



Label kit with legend option

ZARC620

EAN Code: 3606481499448

Main

Range of product	Harmony Pocket Remote
Accessory / separate part type	Front label cover
Accessory / separate part category	Marking accessory

Complementary

Material	Polyester
Length	150 mm
Width	2 mm
Height	270 mm
Depth	0.1 mm
Colour	White/green
Product compatibility	Remote control ZART
Net weight	0.015 kg
Customizable	1
Customizable	Yes
GCR BRIDGE	ZARC600CUST01

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	0.100 cm
Package 1 Width	15.000 cm
Package 1 Length	21.000 cm
Package 1 Weight	19.000 g
Unit Type of Package 2	S01
Number of Units in Package 2	50
Package 2 Height	15.000 cm
Package 2 Width	15.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	995.000 g

Logistical informations

Country of origin SE

Contractual warranty

Warranty 18 months


Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

 Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Under investigation

Use Again

 Repack and remanufacture	
Take-back	No

Offer Marketing Illustration

Product benefits / Features

Features

ZAR Harmony Pocket remote



Offers mobility solutions to improve operator efficiency and reduce installation time

Large set of colors and pictures to customize the front face of your pocket

Suitable for controlling all kinds of machines

Relative humidity 0...95% to -20...55°C operation

Battery life: > 100 h with alkaline batteries

Offer Marketing Illustration

Product benefits / Features

Technical benefits

ZAR Harmony Pocket remote

The Harmony Pocket Remote uses the worldwide free 2.4 GHz frequency to allow unrestricted operation.

Product certifications: CE, UL
Radio certifications: FCC, IC



Users can integrate 3, 4, 6, 8 or 10 buttons according to their needs

IP 67 for the transmitter and IP 66 for the receiver