


Product datasheet

Specifications



white plain cap for flush mounted push button

Local distributor code:

409066742

ZBAF1

EAN Code: 3606481340672

Main

| | |
|---------------------------------------|-------------------------|
| Accessory / separate part category | Marking accessory |
| Accessory / separate part type | Blank push-button cap |
| Product or component type | Antimicrobial plain cap |
| Product compatibility | ZB4FA0 ZB5FA0 |
| Accessory / separate part destination | Push-button head |
| Cap/operator or lens colour | White |
| Shape of signaling unit head | Round |
| Quantity per set | Set of 1 |
| Sale per indivisible quantity | 10 |
| Net weight | 0.001 kg |

Complementary

| | |
|---------------------|---|
| Range compatibility | Harmony XB4 Harmony XAL Harmony XB5 |
| Operator profile | Flush |
| Main group | Push-button Selector switch |

Environment

| | |
|-----------|-----------------------------|
| Standards | ISO 21702 ISO 22196:2011 |
|-----------|-----------------------------|

Packing Units

| | |
|------------------------------|----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 1.600 cm |
| Package 1 Width | 2.200 cm |
| Package 1 Length | 2.200 cm |
| Package 1 Weight | 1.800 g |
| Unit Type of Package 2 | BB1 |
| Number of Units in Package 2 | 10 |
| Package 2 Height | 5.400 cm |

| | |
|-----------------|----------|
| Package 2 Width | 4.200 cm |
|-----------------|----------|

| | |
|------------------|----------|
| Package 2 Length | 5.500 cm |
|------------------|----------|

| | |
|------------------|----------|
| Package 2 Weight | 25.200 g |
|------------------|----------|

Logistical informations

| | |
|-------------------|----|
| Country of origin | FR |
|-------------------|----|

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Total lifecycle Carbon footprint 1

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard Yes

Packaging without single use plastic Yes

[EU RoHS Directive](#) Pro-active compliance (Product out of EU RoHS legal scope)

REACH Regulation [REACH Declaration](#)

Use Again

Repack and remanufacture

End of life manual availability [End of Life Information](#)

Take-back No

Offer Marketing Illustration

Product benefits / Features

Features Harmony XB5



- 

Quick and easy assembly and disassembly
- 

Excellent mechanical connection with operator head
- 

Various types of connection: screw clamp, connector, Faston connector, spring terminal, or printed circuit board
- 

Large set of accessories to customize your panels
- 

Robustness to withstand harsh environments

Offer Marketing Illustration

Product benefits / Features

Technical Benefits

Harmony XB5

Conformity with IEC, UL, CSA, CCC EAC, and JIS standards, as well as CE marking and marine approvals

Up to IP66, 67, 69, 69K, and type 4X protection ratings

High vibration resistance with shake-proof terminal screws



Operating temperature from -40°C to 70°C

Shock protection level up to IK06

Secure switching of inductive or heavy DC loads directly – 100 000 operations at 10A, 24V dc

Image of product / Alternate images

Alternative





