

## PDP67 F 8DI ION

773600



Decentralised input module for PNOZmulti, protection type IP67, connection via connection module, 8 safe digital inputs, 8 outputs configurable as a standard, test pulse or 24 V.

## Technical details

### General data

Approval:	CE, UKCA, cULus Listed, KOSHA, TÜV
Application range:	Standard/failsafe

### Technical data

#### Electrical data

Purpose of U1:	supply
Supply voltage (V):	24 - 24 V
Type of supply voltage U1:	DC
Power consumption DC:	1.2 W
Terminal V ind. loads off:	-45 V
Permitted loads:	Resistive, Inductive, Capacitive

#### Inputs

Number of inputs:	8
Signal level at input at 0:	-3 - +5 VDC
U input to EN 61131-2 Type 1:	24 V DC
Potential isolation input:	No

#### Semiconductor outputs

Function of S/C output:	Test pulse output, 24 VDC output, Standard output
DC voltage at output:	24 V DC
Potential isolation of S/C O:	No

S/C output short circuit proof:	Yes
Environmental data	
Climatic suitability to ...:	EN 60068-2-78
Ambient temperature standard:	EN 60068-2-14
Ambient temperature:	-30 - 60 °C
Storage temperature standard:	EN 60068-2-1/-2
Climatic suitability standard:	EN 60068-2-78
Humidity rating:	93 % r. h. at 40 °C
Condensation permitted?:	Briefly
EMC to standard ...:	EN 61000-4-8, EN 55011: Class A, EN 61000-4-9, EN 61000-4-11, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6, EN 61000-4-2, EN 61000-4-3
Vibration to standard ...:	EN 60068-2-6
Acc. shock to standard1:	15g
Clearance & creepage dist. to:	IEC 60664-1
Overvoltage category:	III
Pollution degree clear.&creep.:	2
Protection type standard:	EN 60529
Mechanical data	
Housing material upper part:	Valox 855
Housing material label holder:	PC
Connection terminal:	M12
Terminal style:	screw interlocked
Height dimension:	133 mm
Width dimension:	60 mm
Depth dimension:	30 mm
Net weight:	250 g
Gross weight:	270 g
Environment	
RoHS directive:	2011/65/EU, 2015/863/EU

RoHS conformity:	yes
RoHS exceptions:	yes
RoHS except.s acc. to direct.:	7C I
REACH compliance:	contains min. 1 SVHC-substance
REACH included substances:	Lead
%-part of the pollutant:	> 0,1 %
CAS No.:	7439-92-1
WEEE klassifikation (08/2018):	5 devices (feed size < 50cm)
<b>Commercial data</b>	
Harmonized System Code:	85389091
EAN-Code:	4046548058901
ECLASS version:	ECLASS-13
ECLASS Reference Feature:	27242604
ETIM Version:	ETIM-9.0
ETIM Reference Group:	EG000024
ETIM Reference Feature:	EC001599
Volume:	0.354

## Obligatory accessories



630298

PSEN cable M12-5sf 20m



630310

PSEN op cable axial M12 5-pole 3m



630297

PSEN op cable axial M12 5-pole 30m



630311

PSEN op cable axial M12 5-pole 5m



630312

PSEN op cable axial M12 5-pole 10m

## Optional accessories



380706

PDP67 cable M12-5sm, 10m



380707

PDP67 cable M12-5sm, 20m



380209

PSS67 Cable M12sf M12sm, 5m



380705

PDP67 cable M12-5sm, 3m








380708







PDP67 cable M12-5sm, 30m



380709

PDP67 cable M12-5sm, 5m

	380250	PSS67 Supply Cable IN sf OUT sm, B, 3m
	380251	PSS67 Supply Cable IN sf OUT sm, B, 5m
	380210	PSS67 Cable M12sf M12sm, 10m
	380200	PSS67 Cable M8sf M12sm, 3m
	380211	PSS67 Cable M12sf M12sm, 30m
	380252	PSS67 Supply Cable IN sf OUT sm, B, 10m
	380220	PSS67 cable M12-5sf, M12-5sm, 20m
	380258	PSS67 Supply Cable IN sf, B, 10m
	380203	PSS67 Cable M8sf M12sm, 30m

	380325	PSEN sl adapter
	380300	PSEN ma adapter
	380256	PSS67 Supply Cable IN sf, B, 3m
	380201	PSS67 Cable M8sf M12sm, 5m
	380301	PSEN cs adapter
	380257	PSS67 Supply Cable IN sf, B, 5m
	380202	PSS67 Cable M8sf M12sm, 10m
	380208	PSS67 Cable M12sf M12sm, 3m