


**Rittal – The System.**

Faster – better – everywhere.



# SZ 2412.216

## Earthing braid

State: 30/04/2025 (Source: [rittal.com/uk-en](http://rittal.com/uk-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# SZ 2412.216 - Earthing braid

Tin-plated copper, in various lengths and cross sections with press-fitted contact rings, earthing straps counteract the current displacement effect at high frequencies, flexible connection opportunities.



## Features

Model No.	SZ 2412.216
Product description	Tin-plated copper, in various lengths and cross-sections with press-fitted contact rings. Earthing braids counteract the current displacement effect at high frequencies, whilst at the same time offering highly flexible connection opportunities.
Cross-section	16 mm <sup>2</sup>
Connection	M8 – M8
Note	Please observe the assembly instructions or PE conductor brochure for the relevant enclosure or case system.
Dimensions	Length: 200 mm
Packs of	10 pc(s).
Net weight	0.36
Gross weight	0.374
Customs tariff number	74198010
EAN	4028177022560
ETIM 9	EC000839
ETIM 8	EC000839
ECLASS 8.0	27062302

# Approvals

---

Approvals

UL + C-UL (listed)