

LEDDriving SL T4W

Ideal replacement for any vehicle



Suitable for various vehicle exterior applications

Available in Cool White



Replaces conventional T4W lamps

Easy upgrade to LED technology with plug & play solutions



Reliable OSRAM quality stands for less lamp replacements

4-year OSRAM guarantee (refer to www.osram.com/am-guarantee for precise conditions)



Suitable LED replacement for T4W

LEDDriving SL T4W replacement lamps offer a modern and intense light with a color temperature up to 6,000 Kelvin. These replacement lamps are suitable for all conventional T4W lamp bases. In comparison to standard lamps, these LED retrofit lamps use up to 80% less energy. OSRAM offers a 4 year guarantee for these LEDDriving SL lamps. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Technical data

Product information

Product type (off-road vs. on-road)	Off-road ≙ T4W
Application (Category and Product specific)	Mainly used for signal/ indicator/ interior applications

General Product Information

Global order reference	3893DWP
------------------------	---------


Electrical Data

Power input	1 W
Nominal voltage	12.0 V
Nominal wattage	1 W
Test voltage	13.5 V
Power input tolerance	±10 %

Photometric Data

Nominal luminous flux	75 lm
Luminous flux tolerance	±25 %
Color temperature	6000 K
Light color LED	Cool white

Physical Attributes & Dimensions



Diameter	9 mm
Product weight	2.70 g
Length	27.4 mm
Lamp base	BA9s

Lifetime Data

Product datasheet

Lifespan B3	1500 hr
Lifespan Tc	4000 hr
Guarantee	4 years

Capabilities

Technology	LED ¹⁾
------------	-------------------

¹⁾ Light-emitting diode lamp

Environmental & Regulatory Information



Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Primary article identifier	4062172150354 4062172401234
Candidate list substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe use instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration no. in SCIP database	dd4362ec-e8fe-4d74-a254-b9aa4f0d5cb9 0c3a666d-6f4f-44ca-ab01-6f003518169b

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172150354	LEDiving SL \triangleq T4W	Blister 2	135 mm x 95 mm x 13 mm	0.22 dm ³	16.00 g
4062172150361	LEDiving SL \triangleq T4W	Shipping carton box 10	71 mm x 104 mm x 146 mm	1.08 dm ³	116.00 g
4062172401234	LEDiving SL \triangleq T4W	BLI ECO 2	95 mm x 17 mm x 135 mm	0.22 dm ³	16.00 g
4062172401241	LEDiving SL \triangleq T4W	Shipping carton box 10	142 mm x 64 mm x 104 mm	0.95 dm ³	106.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

File	
	User instruction GPRS_Safety symbols instructions
	Brochures LEDiving Retrofits - Exchange overview (EN)

Product datasheet

Safety advice

Canbus compatible Coloured lamps for usage behind coloured glass

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

The OSRAM logo is displayed in a bold, orange, sans-serif font.