

64580 1000 W 230 V

Halogen (> 130 V) Double End | Offering a broad portfolio of high quality double end halogen lamps used in the stage and studio markets



Areas of application

- Stage & Theatre
- Studio, TV, & Film
- Professional Photography
- Club & Disco

Product features and benefits

- Robust construction for lasting performance
- Consistent color over the life of the lamps
- Instant on and nearly constant luminous flux over the life of the lamp
- Broad product portfolio supporting the stage and studio markets
- Dimmable with traditional amber shift



Product datasheet

Technical data

General Product Information

ANSI code	-
LIF code	P1/12
Global order reference	64580

Electrical Data

Nominal wattage	1000 W
Nominal voltage	230 V

Photometric Data

Nominal luminous flux	35000 lm
Useful luminous flux (Φ_{use})	31815 lm
Φ_{use} value refers to luminous flux	360
Color temperature	3400 K
Correlated color temperature CCT	3417 K
Chromaticity coordinate x	0.409
Chromaticity coordinate y	0.393
Color rendering index Ra	100

Physical Attributes & Dimensions



Lamp base	R7s
Diameter	12.0 mm
Diameter	12.0 mm
Length	127.1 mm
Length with base excl. base pins/connection	121.70 mm
Product weight	9.67 g

Product datasheet

Operating Conditions

Burning position	p15
Dimmable	Yes

Lifetime Data

Nominal lifetime	15 hr
------------------	-------

Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Primary article identifier	4050300006888
Energy efficiency class	G
Declaration no. in SCIP database	No declarable substances contained
Candidate list substance 1	No declarable substances contained

Country specific information

Product code	METEL code	SEG-No.	STK number	UK Org
4050300006888	OSRH64580	-	4739730	-

Product datasheet

Safety advice

To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminaires designed with suitable mechanisms (protective shields, grids, etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. There must also be a warning sign to indicate that the lamps give off high levels of heat. Detailed information is available on request.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300006888	64580 1000 W 230 V	Folding carton box 1	163 mm x 26 mm x 26 mm	0.42 dm ³	14.93 g
4050300147079	64580 1000 W 230 V	Shipping carton box 12	175 mm x 119 mm x 95 mm	1.98 dm ³	243.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.
